



Ground Science

GEOTECHNICAL INVESTIGATION REPORT

EGSC COMPOST FACILITY, FORGE CREEK

Prepared for SMEC Australia (Docklands, VIC)

4 July 2023

GSSW1879

Reports GSSW1879-1



Ground Science


GROUND SCIENCE SOUTH WEST PTY LTD
ABN: 51 612 825 313
10 Dowsett Street
South Geelong, Vic, 3220
(P) +61 3 5282 1566

TABLE OF CONTENTS

| | | |
|-----|--|---|
| 1.0 | INTRODUCTION | 3 |
| 2.0 | PROJECT BACKGROUND & UNDERSTANDING | 3 |
| 3.0 | SCOPE OF WORK | 3 |
| 4.0 | FIELD INVESTIGATION..... | 4 |
| 5.0 | DISCLOSURE..... | 4 |
| 6.0 | LIMITATIONS | 5 |

APPENDICIES

- APPENDIX A SITE PLAN & DIPPING LOCATIONS
- APPENDIX B LABORATORY TESTING
- APPENDIX C ENGINEERING LOGS



Ground Science

GROUND SCIENCE SOUTH WEST PTY LTD

ABN: 51 612 825 313

10 Dowsett Street

South Geelong, Vic, 3220

(P) +61 3 5282 1566

1.0 INTRODUCTION

Ground Science South West Pty Ltd (Ground Science) has prepared this report to present the results of a limited scope geotechnical investigation undertaken for the project identified as EGSC Compost Facility, located at 175 Johnstons Road, Forge Creek (the site). The scope of works herein was commissioned by SMEC Australia Pty Ltd (the Client).

2.0 PROJECT BACKGROUND & UNDERSTANDING

It is understood the project involves the construction of a new composting facility for the East Gippsland Shire Council, including a site processing shed, a weighbridge, a leachate treatment pond, composting facility and an internal access road with a driveway tie in to the existing Johnstons Road. A site map is provided in Appendix A of this report.

3.0 SCOPE OF WORK

Ground Science was commissioned to excavate a series of pavement dippings, shoulder dippings and test pits within the section defined by our client to establish the existing pavement and subsoil profile. Works were completed inside the private property at 175 Johnstons Road, Forge Creek and along the existing Johnstons Road, Forge Creek. In summary, the following scope of works were performed:

- Excavation of 2 pavement dippings (PD) within the existing Johnstons Road sealed pavement to a target depth of 1.0m or prior refusal;
- Excavation of 2 shoulder dippings (SD) within the existing Johnstons Road unsealed shoulders to a target depth of 1.0m or prior refusal;
- Excavation of 16 test pits (TP) along the proposed internal access road to a target depth of 1.5m below existing surface levels or prior refusal;
- The continuation of 5 of the above test pits to a target depth of 2.0m below existing surface levels or prior refusal, to determine founding conditions of manhole chambers;
- Excavation of 10 test pits (TP) within the proposed hard stand to a target depth of 1.5m below existing surface levels or prior refusal;
- Excavation of 4 test pits (LPTP) to within the proposed leachate treatment pond to a target depth of 3.0m below existing surface levels or prior refusal;
- Each pavement and shoulder dipping was cut by hand using concrete saws, jackhammers and hand augers to ensure an accurate pavement profile determination;
- Each test pit excavated with a 1.7T Yanmar ViO17 excavator using a 300mm wide toothed bucket or a 450mm toothed bucket and a 300mm power auger attachment to ensure a minimum site footprint;
- Logging of pavement/shoulder dippings and test pits and soil profiles in accordance with AS1726 (2017), including depth to bedrock and/or groundwater (where encountered);
- The performance of Dynamic Cone Penetrometer (DCP) tests from the top of subgrade to a depth of 1.5m below or refusal;

Granular fill material from the pavement and shoulder dippings was recovered for laboratory testing including Particle Size Distribution, Atterberg Limits tests, Soaked California Bearing Ratio (CBR) and Field Moisture Content tests.

In-situ subgrade materials from the test pits was recovered for laboratory testing including Particle Size Distribution, Atterberg Limits tests, Soaked California Bearing Ratio (CBR), Triaxial Permeability and Field Moisture Content tests.

A laboratory test summary is provided in Appendix B of this report.



Ground Science

GROUND SCIENCE SOUTH WEST PTY LTD

ABN: 51 612 825 313

10 Dowsett Street

South Geelong, Vic, 3220

(P) +61 3 5282 1566

4.0 FIELD INVESTIGATION

A field investigation was undertaken between the 15th of May and the 19th of May 2023. The locations of the pavement dippings, shoulder dippings and test pits were in accordance with the scope of works.

The site along the existing Johnstons Road was observed to be generally undulating, with shrubs to large-sized vegetation present on both sides of the pavement. Drainage conditions were observed to be generally fair with fair surface runoff. At the time of our investigation, the pavement condition of the existing Johnstons Road was observed to be generally fair. Total fill depth observed in Johnstons Road road reserve varied between 200mm to 800mm below existing surface level.

The site inside of 175 Johnstons Road was observed to be generally undulating. Shrubs were located throughout the proposed test area inside 175 Johnstons Road, with medium to large trees on the fence line surrounding the property and two large trees inside the property boundary. Drainage conditions were observed to be generally poor with poor surface runoff. Total topsoil depth observed in 175 Johnstons Road varied between 200mm to 400mm below existing surface level.

Groundwater was not observed in the scope of the investigation.

An understanding of the regional geological conditions was obtained via review of the GeoVic online seamless geology (2014) map sheet. The results of the review show that the site consists of Pliocene to Quaternary aged alluvial trace deposits overlying the Pliocene to Pleistocene aged Haunted Hills Formation deposits. A boundary between these two units was noted to be located to the north and east of the site. Deposits from both units was observed at the site and have been included in soil classifications of the observed subsoils present in the engineering logs.

Engineering Logs of the pavement dippings, shoulder dippings and test pits are presented in Appendix C of this report.

5.0 DISCLOSURE

This document is detailed for the sole use of the intended recipient(s) or its authorised representatives. Distribution of this report may be carried out at the Clients discretion and must be reproduced in full. Should you have any questions related to this report please do not hesitate to contact the undersigned.

For and on behalf of

Ground Science South West Pty Ltd

AUTHOR:

Michael Knez
Geotechnical Engineer

REVIEWED:

Thomas Seitz
Geotechnical Engineer



Ground Science

GROUND SCIENCE SOUTH WEST PTY LTD

ABN: 51 612 825 313

10 Dowsett Street

South Geelong, Vic, 3220

(P) +61 3 5282 1566

6.0 LIMITATIONS

This type of investigation (as per our commission) is not designed or capable of locating all soil conditions, (which can vary even over short distances). The advice given in this report is based on the assumption that the test results are representative of the overall soil conditions. However, it should be noted that actual conditions in some parts of the Site might differ from those found. If further sampling reveals soil conditions significantly different from those shown in our findings, Ground Science must be consulted.

The scope and the period of Ground Science services are described in the proposal and are subject to restrictions and limitations. Ground Science did not perform a complete assessment of all possible conditions or circumstances that may exist at the site. If a service is not expressly indicated, do not assume it has been provided. If a matter is not addressed, do not assume that any determination has been made by Ground Science South in regards to it.

Where data has been supplied by the client or a third party, it is assumed that the information is correct unless otherwise stated. No responsibility is accepted by Ground Science for incomplete or inaccurate data supplied by others.

It is recognised that the passage of time affects the information and assessment provided in this document. Ground Science's assessment is based on information that existed at the time of the preparation of this document. It is understood that the services provided allowed Ground Science to form no more than an opinion of the actual site conditions observed during sampling and observations of the site visit and cannot be used to assess the effects of any subsequent changes in the quality of the site, or its surroundings, or any laws or regulations.

Any drawings or figures presented in this report should be considered only as pictorial evidence of our work. Therefore, unless otherwise stated, any dimensions should not be used for accurate calculations or dimensioning.

This document is COPYRIGHT- all rights reserved. No part of this document may be reproduced or copied in any form or by means without written permission by Ground Science. All other property in this submission shall not pass until all fees for preparation have been settled. This submission is for the use only of the party to whom it is addressed and for no other purpose. No responsibility is accepted to any third party who may use or rely on the whole or any part of the content of this submission. No responsibility will be taken for this report if it is altered in any way, or not reproduced in full. This document remains the property of Ground Science until all fees and monies have been paid in full.

GROUND SCIENCE SOUTH WEST PTY LTD

ABN: 51 612 825 313

10 Dowsett Street
South Geelong, Vic, 3220
(P) +61 3 5282 1566

APPENDIX A


Site Plan & Dipping Locations

ADVERTISED

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science



GROUND SCIENCE SOUTH WEST PTY LTD

ABN: 51 612 825 313

10 Dowsett Street

South Geelong, Vic, 3220


(P) +61 3 5282 1566

APPENDIX B


Laboratory Testing

ADVERTISED

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science




GROUND SCIENCE SOUTH WEST PTY LTD
ABN: 51 612 825 313
 10 Dowsett Street
 South Geelong, Vic, 3220
 (P) +61 3 5282 1566

LABORATORY TESTING SUMMARY

| | | | |
|------------------|--|-------------------|----------|
| Client: | SMEC AUSTRALIA PTY LTD (DOCKLANDS, VIC) | Job No | GSSW1879 |
| Project: | GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY | Sampled By | MK & GD |
| Location: | FORGE CREEK | | |

| Site No. | Layer (m) | Lab Ref No. | Soil Class. | 75mm | 37.5mm | 19mm | 9.5mm | 4.75mm | 2.36mm | 425um | 75um | Liquid Limit (%) | Plastic Limit (%) | Plasticity Index (%) | Soaked CBR (%) | Swell (%) | Permeability |
|----------|---------------|-------------|-------------|------|--------|------|-------|--------|--------|-------|------|------------------|-------------------|----------------------|----------------|-----------|--------------|
| PD01 | 0.025m - 0.6m | 1879-S1 | GC | 100 | 99 | 83 | 67 | 55 | 49 | 25 | 13 | 23 | 13 | 10 | 30 | 0.0 | - |
| PD02 | 0.025m - 0.3m | 1879-S2 | GM-GC | 100 | 94 | 78 | 63 | 52 | 47 | 28 | 15 | 20 | 12 | 8 | 45 | 0.0 | - |
| SD01 | 0.1m - 0.8m | 1879-S3 | GM-GC | 100 | 96 | 80 | 65 | 54 | 48 | 27 | 14 | 20 | 14 | 6 | 30 | 0.0 | - |
| TP01 | 0.3m - 1.25m | 1879-S4 | CH | - | - | - | - | 100 | 99 | 97 | 91 | 66 | 24 | 42 | 1.5 | 3.0 | - |
| TP02 | 1.15m - 1.8m | 1879-S5 | CL | - | - | - | - | - | 100 | 98 | 90 | 33 | 17 | 16 | - | - | - |
| TP03 | 1.1m - 1.5m | 1879-S6 | CL | - | - | - | 100 | 99 | 99 | 96 | 80 | 31 | 17 | 14 | 5 | 0.5 | - |
| TP04 | 1.2m - 1.9m | 1879-S7 | CI | - | - | - | - | - | 100 | 95 | 81 | 41 | 15 | 26 | - | - | - |
| TP05 | 0.55m - 1.2m | 1879-S8 | CI | - | - | - | - | - | 100 | 91 | 64 | 36 | 14 | 22 | 3.0 | 1.0 | - |
| TP07 | 0.4m - 1.1m | 1879-S9 | CH | - | - | - | - | - | 100 | 95 | 77 | 53 | 19 | 34 | 3.0 | 2.0 | - |
| TP09 | 0.35m - 1.3m | 1879-S10 | CH | - | - | - | - | - | 100 | 93 | 65 | 56 | 19 | 37 | 2.5 | 2.0 | - |

NO – Denotes Not Obtainable
 NP – Denotes Non-Plastic




GROUND SCIENCE SOUTH WEST PTY LTD
ABN: 51 612 825 313
 10 Dowsett Street
 South Geelong, Vic, 3220
 (P) +61 3 5282 1566

LABORATORY TESTING SUMMARY

| | | | |
|------------------|--|-------------------|----------|
| Client: | SMEC AUSTRALIA PTY LTD (DOCKLANDS, VIC) | Job No | GSSW1879 |
| Project: | GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY | Sampled By | MK & GD |
| Location: | FORGE CREEK | | |

| Site No. | Layer (m) | Lab Ref No. | Soil Class. | 75mm | 37.5mm | 19mm | 9.5mm | 4.75mm | 2.36mm | 425um | 75um | Liquid Limit (%) | Plastic Limit (%) | Plasticity Index (%) | Soaked CBR (%) | Swell (%) | Permeability |
|----------|--------------|-------------|-------------|------|--------|------|-------|--------|--------|-------|------|------------------|-------------------|----------------------|----------------|-----------|--------------|
| TP10 | 0.7m - 1.7m | 1879-S11 | CI | - | - | - | - | - | 100 | 97 | 75 | 48 | 17 | 31 | - | - | - |
| TP12 | 1.5m - 1.7m | 1879-S12 | CH | - | 100 | 97 | 94 | 93 | 92 | 88 | 77 | 58 | 15 | 43 | - | - | - |
| TP13 | 0.3m - 1.5m | 1879-S13 | CI | - | - | - | - | - | 100 | 95 | 77 | 50 | 17 | 33 | 3.5 | 1.0 | - |
| TP14 | 1.0m - 1.6m | 1879-S14 | CL | - | - | 100 | 99 | 99 | 98 | 89 | 58 | 34 | 13 | 21 | - | - | - |
| TP15 | 0.6m - 1.25m | 1879-S15 | CI | - | - | - | 100 | 99 | 99 | 90 | 54 | 36 | 12 | 24 | 2.5 | 1.5 | - |
| TP19 | 0.7m - 1.2m | 1879-S16 | CI | - | - | - | - | - | 100 | 96 | 86 | 41 | 17 | 24 | - | - | - |
| TP20 | 1.2m - 1.5m | 1879-S17 | CH | 100 | 95 | 92 | 88 | 84 | 82 | 71 | 62 | 96 | 26 | 70 | - | - | - |
| TP23 | 0.4m - 1.5m | 1879-S18 | CH | - | - | 100 | 99 | 98 | 98 | 92 | 85 | 88 | 27 | 61 | - | - | - |
| TP24 | 0.4m - 1.1m | 1879-S19 | CH | - | 100 | 99 | 97 | 92 | 91 | 58 | 77 | 78 | 47 | 31 | - | - | - |
| TP25 | 0.8m - 1.3m | 1879-S20 | CH | 100 | 97 | 89 | 83 | 78 | 74 | 60 | 50 | 70 | 27 | 43 | - | - | - |

NO – Denotes Not Obtainable
 NP – Denotes Non-Plastic



GROUND SCIENCE SOUTH WEST PTY LTD
ABN: 51 612 825 313
 10 Dowsett Street
 South Geelong, Vic, 3220
 (P) +61 3 5282 1566

LABORATORY TESTING SUMMARY

| | | | |
|------------------|--|-------------------|----------|
| Client: | SMEC AUSTRALIA PTY LTD (DOCKLANDS, VIC) | Job No | GSSW1879 |
| Project: | GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY | Sampled By | MK & GD |
| Location: | FORGE CREEK | | |

| Site No. | Layer (m) | Lab Ref No. | Soil Class. | 75mm | 37.5mm | 19mm | 9.5mm | 4.75mm | 2.36mm | 425um | 75um | Liquid Limit (%) | Plastic Limit (%) | Plasticity Index (%) | Soaked CBR (%) | Swell (%) | Permeability (m/sec) |
|---------------------------|--------------|-------------|-------------|------|--------|------|-------|--------|--------|-------|------|------------------|-------------------|----------------------|----------------|-----------|----------------------|
| LPTP01 | 0.4m - 2.0m | 1879-S21 | CI | - | - | - | - | - | 100 | 90 | 56 | 40 | 12 | 28 | 4.5 | 1.0 | 1x10 ⁻¹⁰ |
| LPTP02 | 1.2m - 3.0m | 1879-S22 | CH | - | - | - | - | - | 100 | 641 | 44 | 61 | 20 | 41 | 2.5 | 2.5 | - |
| LPTP03 | 1.2m - 2.5m | 1879-S23 | CH | - | - | - | - | 100 | 99 | 60 | 45 | 52 | 16 | 36 | 3.0 | 1.5 | - |
| LPTP04 | 0.55m - 2.5m | 1879-S24 | CH | - | - | - | - | - | 100 | 93 | 65 | 61 | 18 | 43 | 1.5 | 2.0 | 4x10 ⁻¹¹ |
| LPTP01 | 0.4m - 2.0m | 1879-S25 | CI | - | - | - | - | - | 100 | 90 | 56 | 40 | 12 | 28 | 4.5 | 1.0 | 9x10 ⁻¹¹ |
| LPTP04 | 0.55m - 2.0m | 1879-S26 | CH | - | - | - | - | - | 100 | 93 | 65 | 61 | 18 | 43 | 1.5 | 2.0 | 2x10 ⁻¹¹ |
| TP19 + TP24 + TP25 + TP26 | 0.4m - 1.5m | 1879-S27 | CH | - | 100 | 99 | 96 | 92 | 80 | 81 | 74 | 69 | 28 | 41 | - | - | 3x10 ⁻¹⁰ |
| TP19 + TP24 + TP25 + TP26 | 0.4m - 1.5m | 1879-S28 | CH | - | 100 | 99 | 96 | 92 | 80 | 81 | 74 | 69 | 28 | 41 | - | - | 2x10 ⁻¹⁰ |

NO – Denotes Not Obtainable
 NP – Denotes Non-Plastic

GROUND SCIENCE SOUTH WEST PTY LTD
ABN: 51 612 825 313
10 Dowsett Street
South Geelong, Vic, 3220
(P) +61 3 5282 1566

APPENDIX C

Engineering Logs

ADVERTISED

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science



Ground Science South West Pavement Investigation Report

ADVERTISED
This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.

Job Information

| | | | |
|------------------------|--|---------------------|-----------------------|
| Client | SMEC AUSTRALIA PTY LTD (DOCKLANDS, VIC) | Job No | GSSW1879 |
| Project | GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY | Site No | PD01 – Westbound Lane |
| Location | FORGE CREEK | Date Sampled | 15/06/2023 |
| GPS Coordinates | -37.878788°, 147.620237° | Sampled By | MK & GD |
| | Offset – 1.2m South of Centre Line | | |

Site Information

| | | | |
|--------------------------|---|--------------------------------------|--------------------------------------|
| Topography | In General – Undulating Locally – Dip | Trees | Shrubs, Small to Large |
| | | Site Code | MS |
| Drainage | In General – Fair Locally – Fair, Vegetation | Drainage Type | RHS: Spoon Drain LHS: Spoon Drain |
| | | Width of Seal Formation Width | 5.3m 7.2m |
| Surface Condition | In General – Fair, Transverse Shape – Fair, Longitudinal Shape – Fair Faults – Rutting <10mm, Slick/Flushing & Edge Drop Off | | |

Field Pavement Profile Logs

| Layer (mm) | | Layer Description | Lab Reference No. | NMC (%) | Depth (mm) |
|------------|------|---|-------------------|---------|------------|
| From | To | | | | |
| 0 | 25 | ASPHALT. | - | - | - |
| 25 | 600 | FILL: GC - sandy, clayey GRAVEL (River Gravel), orange mottled white, sub angular to rounded fine to coarse, low plasticity, sand 36% fine to coarse grained, dense, dry. | 1879-S1, 1879-S29 | 3.5 | 220 |
| 600 | 750 | silty SAND, with gravel, dark brown, fine to coarse grained, low plasticity, gravel rounded fine to coarse, medium dense, dry (inferred alluvial deposits). | - | - | - |
| 750 | 850 | sandy SILT/CLAY, pale grey, low plasticity, sand fine to coarse grained, hard, dry (inferred alluvial deposits). | - | - | - |
| 850 | 1000 | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine grained, gravel fine, very stiff to hard, dry to moist (inferred alluvial deposits). | 1879-S30 | 18.5 | 950 |
| 1000 | - | TERMINATED. | - | - | - |

Laboratory Test Results

| Lab Ref. No. | Soil Class | 75mm | 37.5mm | 19mm | 9.5mm | 4.75mm | 2.36mm | 425µm | 75µm | Liquid Limit (%) | Plastic Limit (%) | Plasticity Index (%) | Soaked CBR (%) | Swell (%) |
|--------------|------------|------|--------|------|-------|--------|--------|-------|------|------------------|-------------------|----------------------|----------------|-----------|
| 1897-S1 | GC | 100 | 99 | 83 | 67 | 55 | 49 | 25 | 13 | 23 | 13 | 10 | 30 | 0.0 |



Ground Science

DYNAMIC CONE PENETROMETER - AS1289 6.3.2

A C N 612 825 313

10 Dowssett Street, South Geelong, VIC 3220

Client: SMEC AUSTRALIA PTY LTD (DOCKLANDS, VIC)

Project: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY

Location: FORGE CREEK

Test Number: -

Test Location: PD01

Datum: 850


Job No: GSSW1879

Report No: GSSW1879-1

Date Tested: 15/05/2023

Tested By: MK & GD

Dynamic Cone Penetrometer (DCP) Profile



Notes:



NATA Accredited Laboratory No. 20109
Accredited for compliance with ISO/IEC 17025 - Testing

Chris Mamalis
Approved Signatory
Date 30-Jun-23



Ground Science South West Pavement Investigation Report

ADVERTISED
This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.

Site Photographs





Ground Science South West Pavement Investigation Report

ADVERTISED
This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.

Site Photographs



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S1
Date Sampled: 15/05/2023
Dates Tested: 24/05/2023 - 07/06/2023
Sampling Method: AS 1289.1.2.1 6.4 (b) - Sampling from layers in earthworks or pavement - compacted
Remarks: Material classified as per AS 1726:2017
Sample Location: PD01, Depth: 0.025m - 0.6m
Material: FILL: GC - sandy, clayey GRAVEL (River Gravel), orange mottled white, sub angular to rounded fine to coarse, low plasticity, sand 36% fine to coarse grained, dense, dry.

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au


Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

Particle Size Distribution (AS1141.11.1)

| Sample Washing | Sample was Washed | | | |
|----------------|-------------------|----------------|------------|-----------------|
| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
| 53 mm | 100 | | 0 | |
| 37.5 mm | 99 | | 1 | |
| 26.5 mm | 91 | | 7 | |
| 19 mm | 83 | | 8 | |
| 13.2 mm | 75 | | 8 | |
| 9.5 mm | 67 | | 8 | |
| 6.7 mm | 59 | | 7 | |
| 4.75 mm | 55 | | 4 | |
| 2.36 mm | 49 | | 6 | |
| 1.18 mm | 42 | | 7 | |
| 0.6 mm | 31 | | 11 | |
| 0.425 mm | 25 | | 6 | |
| 0.3 mm | 21 | | 4 | |
| 0.15 mm | 17 | | 4 | |
| 0.075 mm | 13 | | 4 | |



| Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1) | | Min | Max |
|--|------------|-----|-----|
| Sample History | Oven Dried | | |
| Preparation Method | Dry Sieve | | |
| Liquid Limit (%) | 23 | | |
| Plastic Limit (%) | 13 | | |
| Plasticity Index (%) | 10 | | |

| Linear Shrinkage (AS1289 3.4.1) | | Min | Max |
|----------------------------------|---------------|-----|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | | |
| Linear Shrinkage (%) | 4.0 | | |
| Cracking Crumbling Curling | Cracking | | |

Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S1
Date Sampled: 15/05/2023
Dates Tested: 24/05/2023 - 09/06/2023
Sampling Method: AS 1289.1.2.1 6.4 (b) - Sampling from layers in earthworks or pavement - compacted
Remarks: Material classified as per AS 1726:2017
Sample Location: PD01, Depth: 0.025m - 0.6m
Material: FILL: GC - sandy, clayey GRAVEL (River Gravel), orange mottled white, sub angular to rounded fine to coarse, low plasticity, sand 36% fine to coarse grained, dense, dry.

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au



Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| California Bearing Ratio (AS 1289 6.1.1 & 2.1.1) | | Min | Max |
|--|-----------------------|-----|-----|
| CBR taken at | 2.5 mm | | |
| CBR % | 30 | | |
| Method of Compactive Effort | Modified | | |
| Method used to Determine MDD | AS 1289 5.2.1 & 2.1.1 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Maximum Dry Density (t/m ³) | 2.25 | | |
| Optimum Moisture Content (%) | 6.0 | | |
| Laboratory Density Ratio (%) | 98.0 | | |
| Laboratory Moisture Ratio (%) | 97.5 | | |
| Dry Density after Soaking (t/m ³) | 2.21 | | |
| Field Moisture Content (%) | | | |
| Moisture Content at Placement (%) | 5.9 | | |
| Moisture Content Top 30mm (%) | 6.6 | | |
| Moisture Content Rest of Sample (%) | 6.3 | | |
| Mass Surcharge (kg) | 4.5 | | |
| Soaking Period (days) | 4 | | |
| Curing Hours | 153.2 | | |
| Swell (%) | 0.0 | | |
| Oversize Material (mm) | 19 | | |
| Oversize Material Included | Excluded | | |
| Oversize Material (%) | 16.2 | | |
| Sample remoulded as per Vic Roads Code of Practice RC 500.16 | | | |

| Dry Density - Moisture Relationship (AS 1289 5.2.1 & 2.1.1) | | Min | Max |
|---|-------------------|-----|-----|
| Mould Type | 1 LITRE MOULD A | | |
| Compaction | Modified | | |
| Maximum Dry Density (t/m ³) | 2.25 | | |
| Optimum Moisture Content (%) | 6.0 | | |
| Oversize Sieve (mm) | 19.0 | | |
| Oversize Material Wet (%) | 16 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Curing Hours (h) | 95.1 | | |





Ground Science South West Pavement Investigation Report

ADVERTISED
This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.

Job Information

| | | | | |
|-----------------|--|------------------------------------|-----------------------|---------|
| Client | SMEC AUSTRALIA PTY LTD (DOCKLANDS, VIC) | Job No | GSSW1879 | |
| Project | GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY | Site No | PD02 – Eastbound Lane | |
| Location | FORGE CREEK | Date Sampled | 15/06/2023 | |
| GPS Coordinates | -37.878596°, 147.619039° | Offset – 1.3m North of Centre Line | Sampled By | MK & GD |

Site Information

| | | | |
|-------------------|---|-------------------------------|--------------------------------------|
| Topography | In General – Undulating Locally – Steep Slope | Trees | Shrubs, Small to Large |
| | | Site Code | MS |
| Drainage | In General – Fair Locally – Fair, Vegetation | Drainage Type | RHS: Spoon Drain LHS: Spoon Drain |
| | | Width of Seal Formation Width | 5.2m 7.4m |
| Surface Condition | In General – Fair, Transverse Shape – Fair, Longitudinal Shape – Fair Faults – Rutting <10mm, Slick/Flushing & Edge Drop Off | | |

Field Pavement Profile Logs

| Layer (mm) | | Layer Description | Lab Reference No. | NMC (%) | Depth (mm) |
|------------|------|--|-------------------|---------|------------|
| From | To | | | | |
| 0 | 25 | SPRAY SEAL | - | - | - |
| 25 | 300 | FILL: GM-GC - sandy, silty/clayey GRAVEL (River Gravel), orange mottled white, sub angular to rounded fine to coarse, low plasticity, sand 32% fine to coarse grained, dense, dry. | 1879-S2, 1879-S33 | 3.6 | 210 |
| 300 | 1000 | CLAY, trace sand, orange mottled brown, low plasticity, sand fine grained, gravel fine, stiff to very stiff, moist (inferred alluvial deposits). | 1879-S34 | 13.9 | 950 |
| 1000 | - | TERMINATED. | - | - | - |

Laboratory Test Results

| Lab Ref. No. | Soil Class | 75mm | 37.5mm | 19mm | 9.5mm | 4.75mm | 2.36mm | 425µm | 75µm | Liquid Limit (%) | Plastic Limit (%) | Plasticity Index (%) | Soaked CBR (%) | Swell (%) |
|--------------|------------|------|--------|------|-------|--------|--------|-------|------|------------------|-------------------|----------------------|----------------|-----------|
| 1897-S2 | GM-GC | 100 | 94 | 78 | 63 | 52 | 47 | 28 | 15 | 20 | 12 | 8 | 45 | 0.0 |



Ground Science

DYNAMIC CONE PENETROMETER - AS1289 6.3.2

A C N 612 825 313

10 Dowssett Street, South Geelong, VIC 3220

Client: SMEC AUSTRALIA PTY LTD (DOCKLANDS, VIC)

Project: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY

Location: FORGE CREEK

Test Number: -

Test Location: PD02

Datum: 300


Job No: GSSW1879

Report No: GSSW1879-1

Date Tested: 15/05/2023

Tested By: MK & GD

Dynamic Cone Penetrometer (DCP) Profile



Notes:



NATA Accredited Laboratory No. 20109
Accredited for compliance with ISO/IEC 17025 - Testing


Chris Mamalis
Approved Signatory
Date 30-Jun-23



Ground Science South West Pavement Investigation Report

ADVERTISED
This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.

Site Photographs





Ground Science South West Pavement Investigation Report

ADVERTISED
This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.

Site Photographs



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S2
Date Sampled: 15/05/2023
Dates Tested: 24/05/2023 - 07/06/2023
Sampling Method: AS 1289.1.2.1 6.4 (b) - Sampling from layers in earthworks or pavement - compacted
Remarks: Material classified as per AS 1726:2017
Sample Location: PD02, Depth: 0.025m - 0.3m
Material: FILL: GM-GC - sandy, silty/clayey GRAVEL (River Gravel), orange mottled white, sub angular to rounded fine to coarse, low plasticity, sand 32% fine to coarse grained, dense, dry.


Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| Particle Size Distribution (AS1141.11.1) | | | | |
|--|-------------------|----------------|------------|-----------------|
| Sample Washing | Sample was Washed | | | |
| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
| 75 mm | 100 | | 0 | |
| 63 mm | 98 | | 2 | |
| 53 mm | 98 | | 0 | |
| 37.5 mm | 94 | | 4 | |
| 26.5 mm | 88 | | 6 | |
| 19 mm | 78 | | 9 | |
| 13.2 mm | 70 | | 8 | |
| 9.5 mm | 63 | | 7 | |
| 6.7 mm | 57 | | 7 | |
| 4.75 mm | 52 | | 4 | |
| 2.36 mm | 47 | | 5 | |
| 1.18 mm | 41 | | 6 | |
| 0.6 mm | 33 | | 8 | |
| 0.425 mm | 28 | | 5 | |
| 0.3 mm | 24 | | 4 | |
| 0.15 mm | 20 | | 4 | |
| 0.075 mm | 15 | | 5 | |



| Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1) | | Min | Max |
|--|------------|-----|-----|
| Sample History | Oven Dried | | |
| Preparation Method | Dry Sieve | | |
| Liquid Limit (%) | 20 | | |
| Plastic Limit (%) | 12 | | |
| Plasticity Index (%) | 8 | | |

| Linear Shrinkage (AS1289 3.4.1) | | Min | Max |
|----------------------------------|---------------|-----|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | | |
| Linear Shrinkage (%) | 3.0 | | |
| Cracking Crumbling Curling | Cracking | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S2
Date Sampled: 15/05/2023
Dates Tested: 24/05/2023 - 09/06/2023
Sampling Method: AS 1289.1.2.1 6.4 (b) - Sampling from layers in earthworks or pavement - compacted
Remarks: Material classified as per AS 1726:2017
Sample Location: PD02, Depth: 0.025m - 0.3m
Material: FILL: GM-GC - sandy, silty/clayey GRAVEL (River Gravel), orange mottled white, sub angular to rounded fine to coarse, low plasticity, sand 32% fine to coarse graded, dense, dry.

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au



Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| California Bearing Ratio (AS 1289 6.1.1 & 2.1.1) | | Min | Max |
|--|-----------------------|-----|-----|
| CBR taken at | 5 mm | | |
| CBR % | 45 | | |
| Method of Compactive Effort | Modified | | |
| Method used to Determine MDD | AS 1289 5.2.1 & 2.1.1 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Maximum Dry Density (t/m ³) | 2.22 | | |
| Optimum Moisture Content (%) | 6.0 | | |
| Laboratory Density Ratio (%) | 98.5 | | |
| Laboratory Moisture Ratio (%) | 96.5 | | |
| Dry Density after Soaking (t/m ³) | 2.18 | | |
| Field Moisture Content (%) | | | |
| Moisture Content at Placement (%) | 5.7 | | |
| Moisture Content Top 30mm (%) | 6.4 | | |
| Moisture Content Rest of Sample (%) | 6.9 | | |
| Mass Surcharge (kg) | 4.5 | | |
| Soaking Period (days) | 4 | | |
| Curing Hours | 56.7 | | |
| Swell (%) | 0.0 | | |
| Oversize Material (mm) | 19 | | |
| Oversize Material Included | Excluded | | |
| Oversize Material (%) | 21.1 | | |
| Sample remoulded as per Vic Roads Code of Practice RC 500.16 | | | |

| Dry Density - Moisture Relationship (AS 1289 5.2.1 & 2.1.1) | | Min | Max |
|---|-------------------|-----|-----|
| Mould Type | 1 LITRE MOULD A | | |
| Compaction | Modified | | |
| Maximum Dry Density (t/m ³) | 2.22 | | |
| Optimum Moisture Content (%) | 6.0 | | |
| Oversize Sieve (mm) | 19.0 | | |
| Oversize Material Wet (%) | 21 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Curing Hours (h) | 94.9 | | |





Ground Science South West Pavement Investigation Report

ADVERTISED
This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.

Job Information

| | | | | |
|-----------------|--|----------------------------------|---------------------------|---------|
| Client | SMEC AUSTRALIA PTY LTD (DOCKLANDS, VIC) | Job No | GSSW1879 | |
| Project | GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY | Site No | SD01 – Westbound Shoulder | |
| Location | FORGE CREEK | Date Sampled | 15/06/2023 | |
| GPS Coordinates | -37.878930°, 147.620995° | Offset – 0.8m South of Edge Line | Sampled By | MK & GD |

Site Information

| | | | |
|-------------------|---|-------------------------------|--------------------------------------|
| Topography | In General – Undulating Locally – Dip | Trees | Shrubs, Small to Large |
| | | Site Code | SH |
| Drainage | In General – Fair Locally – Fair, Vegetation | Drainage Type | RHS: Spoon Drain LHS: Spoon Drain |
| | | Width of Seal Formation Width | 5.3m 7.3m |
| Surface Condition | In General – Fair, Transverse Shape – Fair, Longitudinal Shape – Fair Faults – Rutting <10mm, Slick/Flushing & Edge Drop Off | | |

Field Pavement Profile Logs

| Layer (mm) | | Layer Description | Lab Reference No. | NMC (%) | Depth (mm) |
|------------|-----|--|------------------------------|----------|------------|
| From | To | | | | |
| 0 | 100 | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft to firm, moist, organics. | - | - | - |
| 100 | 800 | FILL: GM-GC - sandy, silty/clayey GRAVEL (River Gravel), orange mottled white, sub angular to rounded fine to coarse, low plasticity, sand 34% fine to coarse grained, dense, dry. | 1879-S3 1879-S31,1798-S32 | 5.2, 5.7 | 200, 780 |
| 800 | - | REFUSAL. | - | - | - |

Laboratory Test Results

| Lab Ref. No. | Soil Class | 75mm | 37.5mm | 19mm | 9.5mm | 4.75mm | 2.36mm | 425µm | 75µm | Liquid Limit (%) | Plastic Limit (%) | Plasticity Index (%) | Soaked CBR (%) | Swell (%) |
|--------------|------------|------|--------|------|-------|--------|--------|-------|------|------------------|-------------------|----------------------|----------------|-----------|
| 1897-S3 | GM-GC | 100 | 96 | 80 | 65 | 54 | 48 | 27 | 14 | 20 | 14 | 6 | 30 | 0.0 |



Ground Science

DYNAMIC CONE PENETROMETER - AS1289 6.3.2

A C N 612 825 313

10 Dowslett Street, South Geelong, VIC 3220

Client: SMEC AUSTRALIA PTY LTD (DOCKLANDS, VIC)

Project: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY

Location: FORGE CREEK

Test Number: -

Test Location: SD01

Datum: 800

Job No: GSSW1879


Report No: GSSW1879-1

Date Tested: 15/05/2023

Tested By: MK & GD

Dynamic Cone Penetrometer (DCP) Profile

No. of Blows



Notes: Immediate Refusal on GRAVEL



NATA Accredited Laboratory No. 20109
Accredited for compliance with ISO/IEC 17025 - Testing

Chris Mamalis
Approved Signatory
Date 30-Jun-23



Ground Science South West Pavement Investigation Report

ADVERTISED
This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.

Site Photographs





Ground Science South West Pavement Investigation Report

ADVERTISED
This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.

Site Photographs



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S3
Date Sampled: 15/05/2023
Dates Tested: 24/05/2023 - 08/06/2023
Sampling Method: AS 1289.1.2.1 6.4 (b) - Sampling from layers in earthworks or pavement - compacted
Remarks: Material classified as per AS 1726:2017
Sample Location: SD01, Depth: 0.1m - 0.8m
Material: FILL: GM-GC - sandy, silty/clayey GRAVEL (River Gravel), orange mottled white, sub angular to rounded fine to coarse, low plasticity, sand 34% fine to coarse grained, dense, dry.


Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing




Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| Particle Size Distribution (AS1141.11.1) | | | | |
|--|-------------------|----------------|------------|-----------------|
| Sample Washing | Sample was Washed | | | |
| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
| 63 mm | 100 | | 0 | |
| 53 mm | 99 | | 1 | |
| 37.5 mm | 96 | | 3 | |
| 26.5 mm | 91 | | 5 | |
| 19 mm | 80 | | 12 | |
| 13.2 mm | 73 | | 6 | |
| 9.5 mm | 65 | | 8 | |
| 6.7 mm | 58 | | 7 | |
| 4.75 mm | 54 | | 5 | |
| 2.36 mm | 48 | | 6 | |
| 1.18 mm | 42 | | 7 | |
| 0.6 mm | 32 | | 10 | |
| 0.425 mm | 27 | | 5 | |
| 0.3 mm | 23 | | 4 | |
| 0.15 mm | 19 | | 4 | |
| 0.075 mm | 14 | | 5 | |



| Atterberg Limit (AS1289 3.1.1 & 3.2.1 & 3.3.1) | | Min | Max |
|--|------------|-----|-----|
| Sample History | Oven Dried | | |
| Preparation Method | Dry Sieve | | |
| Liquid Limit (%) | 20 | | |
| Plastic Limit (%) | 14 | | |
| Plasticity Index (%) | 6 | | |

| Linear Shrinkage (AS1289 3.4.1) | | Min | Max |
|----------------------------------|---------------|-----|-----|
| Moisture Condition Determined By | AS 1289.3.1.1 | | |
| Linear Shrinkage (%) | 3.0 | | |
| Cracking Crumbling Curling | Cracking | | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S3
Date Sampled: 15/05/2023
Dates Tested: 24/05/2023 - 09/06/2023
Sampling Method: AS 1289.1.2.1 6.4 (b) - Sampling from layers in earthworks or pavement - compacted
Remarks: Material classified as per AS 1726:2017
Sample Location: SD01, Depth: 0.1m - 0.8m
Material: FILL: GM-GC - sandy, silty/clayey GRAVEL (River Gravel), orange mottled white, sub angular to rounded fine to coarse, low plasticity, sand 34% fine to coarse graded, dense, dry.

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au



Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| California Bearing Ratio (AS 1289 6.1.1 & 2.1.1) | | Min | Max |
|--|-----------------------|-----|-----|
| CBR taken at | 5 mm | | |
| CBR % | 30 | | |
| Method of Compactive Effort | Modified | | |
| Method used to Determine MDD | AS 1289 5.2.1 & 2.1.1 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Maximum Dry Density (t/m ³) | 2.19 | | |
| Optimum Moisture Content (%) | 6.5 | | |
| Laboratory Density Ratio (%) | 98.0 | | |
| Laboratory Moisture Ratio (%) | 103.0 | | |
| Dry Density after Soaking (t/m ³) | 2.14 | | |
| Field Moisture Content (%) | | | |
| Moisture Content at Placement (%) | 6.6 | | |
| Moisture Content Top 30mm (%) | 7.2 | | |
| Moisture Content Rest of Sample (%) | 6.9 | | |
| Mass Surcharge (kg) | 4.5 | | |
| Soaking Period (days) | 4 | | |
| Curing Hours | 152.4 | | |
| Swell (%) | 0.0 | | |
| Oversize Material (mm) | 19 | | |
| Oversize Material Included | Excluded | | |
| Oversize Material (%) | 19.5 | | |
| Sample remoulded as per Vic Roads Code of Practice RC 500.16 | | | |

| Dry Density - Moisture Relationship (AS 1289 5.2.1 & 2.1.1) | | Min | Max |
|---|-------------------|-----|-----|
| Mould Type | 1 LITRE MOULD A | | |
| Compaction | Modified | | |
| Maximum Dry Density (t/m ³) | 2.19 | | |
| Optimum Moisture Content (%) | 6.5 | | |
| Oversize Sieve (mm) | 19.0 | | |
| Oversize Material Wet (%) | 20 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Curing Hours (h) | 94.7 | | |





Ground Science South West Pavement Investigation Report

ADVERTISED
This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.

Job Information

| | | | | |
|-----------------|--|----------------------------------|---------------------------|---------|
| Client | SMEC AUSTRALIA PTY LTD (DOCKLANDS, VIC) | Job No | GSSW1879 | |
| Project | GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY | Site No | SD02 – Westbound Shoulder | |
| Location | FORGE CREEK | Date Sampled | 15/06/2023 | |
| GPS Coordinates | -37.878729°, 147.619590° | Offset – 1.4m South of Edge Line | Sampled By | MK & GD |

Site Information

| | | | |
|-------------------|---|-------------------------------|--------------------------------------|
| Topography | In General – Undulating Locally – Steep Slope | Trees | Shrubs, Small to Large |
| | | Site Code | SH |
| Drainage | In General – Fair Locally – Fair, Vegetation | Drainage Type | RHS: Spoon Drain LHS: Spoon Drain |
| | | Width of Seal Formation Width | 5.3m 7.3m |
| Surface Condition | In General – Fair, Transverse Shape – Fair, Longitudinal Shape – Fair Faults – Rutting <10mm, Slick/Flushing & Edge Drop Off | | |

Field Pavement Profile Logs

| Layer (mm) | | Layer Description | Lab Reference No. | NMC (%) | Depth (mm) |
|------------|------|---|-------------------|---------|------------|
| From | To | | | | |
| 0 | 100 | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft to firm, moist, organics. | - | - | - |
| 100 | 200 | sandy, silty/clayey GRAVEL (River Gravel), orange mottled white, sub angular to rounded fine to coarse, low plasticity, sand fine to coarse grained, dense, dry. | 1879-S35 | 7.3 | 150 |
| 200 | 1000 | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine grained, gravel fine, stiff to very stiff, dry to moist (inferred alluvial deposits). | 1879-S36 | 17.2 | 900 |
| 1000 | - | TERMINATED. | - | - | - |

Laboratory Test Results

| Lab Ref. No. | Soil Class | 75mm | 37.5mm | 19mm | 9.5mm | 4.75mm | 2.36mm | 425µm | 75µm | Liquid Limit (%) | Plastic Limit (%) | Plasticity Index (%) | Soaked CBR (%) | Swell (%) |
|--------------|------------|------|--------|------|-------|--------|--------|-------|------|------------------|-------------------|----------------------|----------------|-----------|
| - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |



Ground Science

DYNAMIC CONE PENETROMETER - AS1289 6.3.2

A C N 612 825 313

10 Dowssett Street, South Geelong, VIC 3220

Client: SMEC AUSTRALIA PTY LTD (DOCKLANDS, VIC)

Project: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY

Location: FORGE CREEK

Test Number: -

Test Location: SD02

Datum: 250


Job No: GSSW1879

Report No: GSSW1879-1

Date Tested: 15/05/2023

Tested By: MK & GD

Dynamic Cone Penetrometer (DCP) Profile



Notes:



NATA Accredited Laboratory No. 20109
Accredited for compliance with ISO/IEC 17025 - Testing

Chris Mamalis
Approved Signatory
Date 30-Jun-23



Ground Science South West Pavement Investigation Report

ADVERTISED
This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.

Site Photographs






Ground Science South West Pavement Investigation Report

ADVERTISED
This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.

Site Photographs



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566



Engineering Log Testpit

Testpit No: TP01

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.879078 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.619412 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.5m | Reviewed By : | Location : FORGE CREEK |
| | Date : 16/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-----------|-----------|-------------|---------------------|--|-------------|----------|-------------|
| | | | | | | | Bulk Sample |
| 1 | 0.3 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft to firm, moist, organics. | S-F | M | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 3 | 0.5 | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand 8% fine grained, gravel 1%, stiff to very stiff, moist (inferred alluvial deposits). | St-VSt | M | |
| 4 | | | | | | | |
| 5 | | | | | | | |
| 5 | | | | | | | |
| 5 | | | | | | | |
| 5 | | | | | | | |
| 6 | 1 | | CI | CLAY, trace sand, orange mottled grey, medium plasticity, sand fine to medium grained, very stiff to hard, moist (inferred alluvial deposits). | VSt-H | M | 1879-S4 |
| 6 | | | | | | | |
| 8 | | | | | | | |
| 12 | 1.25 | | | | | | |
| 15 | | | | | | | |
| 20 | | | | | | | |
| R | 1.5 | | | TP01 Terminated at 1.5m | | | |
| | 2 | | | | | | |
| | 2.5 | | | | | | |
| | 3 | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




GroundScience

 (03) 5282 1566
 10 Dowsett St.
 South Geelong, Victoria 3220
 admin@groundscience.com.au

| | | | |
|--------------------------|-----------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP01 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S4
Date Sampled: 16/05/2023
Dates Tested: 24/05/2023 - 13/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP01, Depth: 0.3m - 1.25m
Material: CH - CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand 8% fine grained, gravel 1%, stiff to very stiff, moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

Particle Size Distribution (AS1289 3.6.1)


| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
|----------|----------|----------------|------------|-----------------|
| 9.5 mm | 100 | | 0 | |
| 6.7 mm | 100 | | 0 | |
| 4.75 mm | 100 | | 0 | |
| 2.36 mm | 99 | | 0 | |
| 1.18 mm | 99 | | 0 | |
| 0.6 mm | 98 | | 1 | |
| 0.425 mm | 97 | | 1 | |
| 0.3 mm | 96 | | 1 | |
| 0.15 mm | 94 | | 2 | |
| 0.075 mm | 91 | | 3 | |

Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1)

| | Min | Max |
|----------------------|------------|-----|
| Sample History | Oven Dried | |
| Preparation Method | Dry Sieve | |
| Liquid Limit (%) | 66 | |
| Plastic Limit (%) | 24 | |
| Plasticity Index (%) | 42 | |

Linear Shrinkage (AS1289 3.4.1)

| | Min | Max |
|----------------------------------|--------------------|-----|
| Moisture Condition Determined By | AS 1289.3.1.1 | |
| Linear Shrinkage (%) | 14.0 | |
| Cracking Crumbling Curling | Cracking & Curling | |



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S4
Date Sampled: 16/05/2023
Dates Tested: 24/05/2023 - 19/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP01, Depth: 0.3m - 1.25m
Material: CH - CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand 8% fine grained, gravel 1%, stiff to very stiff, moist (inferred alluvial deposits).

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au



Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| California Bearing Ratio (AS 1289 6.1.1 & 2.1.1) | | Min | Max |
|--|-----------------------|-----|-----|
| CBR taken at | 2.5 mm | | |
| CBR % | 1.5 | | |
| Method of Compactive Effort | Standard | | |
| Method used to Determine MDD | AS 1289 5.1.1 & 2.1.1 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Maximum Dry Density (t/m ³) | 1.51 | | |
| Optimum Moisture Content (%) | 26.0 | | |
| Laboratory Density Ratio (%) | 98.5 | | |
| Laboratory Moisture Ratio (%) | 101.5 | | |
| Dry Density after Soaking (t/m ³) | 1.45 | | |
| Field Moisture Content (%) | | | |
| Moisture Content at Placement (%) | 26.4 | | |
| Moisture Content Top 30mm (%) | 33.8 | | |
| Moisture Content Rest of Sample (%) | 26.5 | | |
| Mass Surcharge (kg) | 4.5 | | |
| Soaking Period (days) | 4 | | |
| Curing Hours | 381.8 | | |
| Swell (%) | 3.0 | | |
| Oversize Material (mm) | 19 | | |
| Oversize Material Included | Excluded | | |
| Oversize Material (%) | 0.0 | | |
| Sample remoulded as per Vic Roads Code of Practice RC 500.16 | | | |

| Dry Density - Moisture Relationship (AS 1289 5.1.1 & 2.1.1) | | Min | Max |
|---|-------------------|-----|-----|
| Mould Type | 1 LITRE MOULD A | | |
| Compaction | Standard | | |
| Maximum Dry Density (t/m ³) | 1.51 | | |
| Optimum Moisture Content (%) | 26.0 | | |
| Oversize Sieve (mm) | 19.0 | | |
| Oversize Material Wet (%) | 0 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Curing Hours (h) | 197.2 | | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




 (03) 5282 1566
 10 Dowsett St.
 South Geelong, Victoria 3220
 admin@groundscience.com.au

| | | | |
|--------------------------|-----------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP02 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S5
Date Sampled: 16/05/2023
Dates Tested: 24/05/2023 - 08/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP02, Depth: 1.15m - 1.8m
Material: CL - CLAY, trace sand, orange mottled grey, low plasticity, sand 10% fine to medium grained, very stiff to hard, moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing




Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| Particle Size Distribution (AS1289 3.6.1) | | | | |
|---|----------|----------------|------------|-----------------|
| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
| 4.75 mm | 100 | | 0 | |
| 2.36 mm | 100 | | 0 | |
| 1.18 mm | 100 | | 0 | |
| 0.6 mm | 99 | | 1 | |
| 0.425 mm | 98 | | 1 | |
| 0.3 mm | 97 | | 1 | |
| 0.15 mm | 96 | | 2 | |
| 0.075 mm | 90 | | 6 | |

| Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1) | | Min | Max |
|--|------------|-----|-----|
| Sample History | Oven Dried | | |
| Preparation Method | Dry Sieve | | |
| Liquid Limit (%) | 33 | | |
| Plastic Limit (%) | 17 | | |
| Plasticity Index (%) | 16 | | |

| Linear Shrinkage (AS1289 3.4.1) | | Min | Max |
|----------------------------------|---------------|-----|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | | |
| Linear Shrinkage (%) | 6.0 | | |
| Cracking Crumbling Curling | Cracking | | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.

| DCP graph | | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-----------|--|-----------|-------------|---------------------|---|-------------|----------|-------------|
| | | | | | | | | Bulk Sample |
| 2 | | 0.3 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, firm, moist, organics. | F | M | |
| 2 | | | | | | | | |
| 2 | | | | | | | | |
| 2 | | 0.5 | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, stiff to very stiff, dry to moist (inferred alluvial deposits). | St-VSt | D-M | |
| 2 | | | | | | | | |
| 2 | | | | | | | | |
| 3 | | | | | | | | |
| 3 | | | | | | | | |
| 4 | | | | | | | | |
| 8 | | 1.1 | | CL | CLAY, with sand, trace gravel, orange mottled brown, low plasticity, sand 19% fine to medium grained, gravel 1%, hard, dry to moist (inferred alluvial deposits). | H | D-M | |
| 10 | | | | | | | | |
| 13 | | | | | | | | |
| 16 | | | | | | | | |
| 19 | | 1.5 | | | TP03 Terminated at 1.5m | | | 1879-S6 |
| | | 2 | | | | | | |
| | | 2.5 | | | | | | |
| | | 3 | | | | | | |


Engineering Log - Testpit

Testpit No: TP03

Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.879415 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.620494 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.5m | Reviewed By : | Location : FORGE CREEK |
| | Date : 16/05/2023 | Loc Comment : |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




 (03) 5282 1566
 10 Dowsett St.
 South Geelong, Victoria 3220
 admin@groundscience.com.au

| | | | |
|--------------------------|------------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMEC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP03 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S6
Date Sampled: 16/05/2023
Dates Tested: 24/05/2023 - 08/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP03, Depth: 1.1m - 1.5m
Material: CL - CLAY, with sand, trace gravel, orange mottled brown, low plasticity, sand 19% fine to medium grained, gravel 1%, hard, dry to moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

Particle Size Distribution (AS1289 3.6.1)


| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
|----------|----------|----------------|------------|-----------------|
| 19 mm | 100 | | 0 | |
| 13.2 mm | 100 | | 0 | |
| 9.5 mm | 100 | | 0 | |
| 6.7 mm | 99 | | 0 | |
| 4.75 mm | 99 | | 0 | |
| 2.36 mm | 99 | | 0 | |
| 1.18 mm | 98 | | 1 | |
| 0.6 mm | 97 | | 1 | |
| 0.425 mm | 96 | | 1 | |
| 0.3 mm | 95 | | 1 | |
| 0.15 mm | 93 | | 2 | |
| 0.075 mm | 80 | | 13 | |

Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1)

| | Min | Max |
|----------------------|------------|-----|
| Sample History | Oven Dried | |
| Preparation Method | Dry Sieve | |
| Liquid Limit (%) | 31 | |
| Plastic Limit (%) | 17 | |
| Plasticity Index (%) | 14 | |

Linear Shrinkage (AS1289 3.4.1)

| | Min | Max |
|----------------------------------|---------------|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | |
| Linear Shrinkage (%) | 5.5 | |
| Cracking Crumbling Curling | Cracking | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S6
Date Sampled: 16/05/2023
Dates Tested: 24/05/2023 - 19/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP03, Depth: 1.1m - 1.5m
Material: CL - CLAY, with sand, trace gravel, orange mottled brown, low plasticity, sand 19% fine to medium grained, gravel 1%, hard, dry to moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au



Accredited for compliance with ISO/IEC 17025 - Testing




Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| California Bearing Ratio (AS 1289 6.1.1 & 2.1.1) | | Min | Max |
|--|-----------------------|-----|-----|
| CBR taken at | 5 mm | | |
| CBR % | 5 | | |
| Method of Compactive Effort | Standard | | |
| Method used to Determine MDD | AS 1289 5.1.1 & 2.1.1 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Maximum Dry Density (t/m ³) | 1.71 | | |
| Optimum Moisture Content (%) | 18.0 | | |
| Laboratory Density Ratio (%) | 98.0 | | |
| Laboratory Moisture Ratio (%) | 101.5 | | |
| Dry Density after Soaking (t/m ³) | 1.67 | | |
| Field Moisture Content (%) | | | |
| Moisture Content at Placement (%) | 18.2 | | |
| Moisture Content Top 30mm (%) | 21.8 | | |
| Moisture Content Rest of Sample (%) | 18.5 | | |
| Mass Surcharge (kg) | 4.5 | | |
| Soaking Period (days) | 4 | | |
| Curing Hours | 380.6 | | |
| Swell (%) | 0.5 | | |
| Oversize Material (mm) | 19 | | |
| Oversize Material Included | Excluded | | |
| Oversize Material (%) | 0.0 | | |
| Sample remoulded as per Vic Roads Code of Practice RC 500.16 | | | |

| Dry Density - Moisture Relationship (AS 1289 5.1.1 & 2.1.1) | | Min | Max |
|---|-------------------|-----|-----|
| Mould Type | 1 LITRE MOULD A | | |
| Compaction | Standard | | |
| Maximum Dry Density (t/m ³) | 1.71 | | |
| Optimum Moisture Content (%) | 18.0 | | |
| Oversize Sieve (mm) | 19.0 | | |
| Oversize Material Wet (%) | 0 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Curing Hours (h) | 260.2 | | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566


Engineering Log - Testpit

Testpit No: TP04

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.879784 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.620746 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.9m | Reviewed By : | Location : FORGE CREEK |
| | Date : 16/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-----------|-----------|-------------|---------------------|--|-------------|----------|-------------|
| | | | | | | | Bulk Sample |
| 2 | 0.3 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, firm, moist, organics. | F | M | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 12 | 0.5 | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, stiff to very stiff, moist (inferred alluvial deposits). | VSt-H | D | |
| 12 | | | | | | | |
| 9 | | | | | | | |
| 8 | | | | | | | |
| 9 | 0.8 | | CI | CLAY, with sand, orange mottled grey, medium plasticity, sand 19% fine to medium grained, stiff to very stiff, dry to moist (inferred alluvial deposits). | St-VSt | D-M | |
| 6 | | | | | | | |
| 6 | | | | | | | |
| 7 | 1.2 | | CI | CLAY, with sand, orange mottled grey, medium plasticity, sand 19% fine to medium grained, very stiff to hard, moist (inferred alluvial deposits). | VSt-H | M | |
| 7 | | | | | | | |
| 7 | | | | | | | |
| 7 | 1.5 | | CI | CLAY, with sand, orange mottled grey, medium plasticity, sand 19% fine to medium grained, very stiff to hard, moist (inferred alluvial deposits). | VSt-H | M | |
| 8 | | | | | | | |
| 13 | | | | | | | |
| | 2 | | | TP04 refusal at 1.9m | | | 1879-S7 |
| | 2.5 | | | | | | |
| | 3 | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




GroundScience

(03) 5282 1566

10 Dowsett St.
South Geelong, Victoria 3220

admin@groundscience.com.au

| | | | |
|--------------------------|------------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMEC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP04 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S7
Date Sampled: 16/05/2023
Dates Tested: 24/05/2023 - 07/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP04, Depth: 1.2m - 1.9m
Material: Cl - CLAY, with sand, orange mottled grey, medium plasticity, sand 19% fine to medium grained, very stiff to hard, moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

Particle Size Distribution (AS1289 3.6.1)


| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
|----------|----------|----------------|------------|-----------------|
| 4.75 mm | 100 | | 0 | |
| 2.36 mm | 100 | | 0 | |
| 1.18 mm | 100 | | 0 | |
| 0.6 mm | 98 | | 2 | |
| 0.425 mm | 95 | | 2 | |
| 0.3 mm | 93 | | 3 | |
| 0.15 mm | 89 | | 4 | |
| 0.075 mm | 81 | | 7 | |

Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1)


| | Min | Max |
|----------------------|------------|-----|
| Sample History | Oven Dried | |
| Preparation Method | Dry Sieve | |
| Liquid Limit (%) | 41 | |
| Plastic Limit (%) | 15 | |
| Plasticity Index (%) | 26 | |

Linear Shrinkage (AS1289 3.4.1)

| | Min | Max |
|----------------------------------|---------------|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | |
| Linear Shrinkage (%) | 8.5 | |
| Cracking Crumbling Curling | Curling | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566


Engineering Log - Testpit

Testpit No: TP05

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.880239 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.620563 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.5m | Reviewed By : | Location : FORGE CREEK |
| | Date : 16/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-------------------------|-----------|-------------|---------------------|--|-------------|----------|-------------|
| | | | | | | | Bulk Sample |
| 1 | 0.3 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft to firm, moist, organics. | S-F | M | |
| 2 | | | | | | | |
| 1 | | | | | | | |
| 3 | 0.55 | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, stiff, moist (inferred alluvial deposits). | St | M | |
| 3 | | | | | | | |
| 4 | | | | | | | |
| 6 | 1.2 | | CI | sandy CLAY, orange mottled brown, medium plasticity, sand 36% fine to coarse grained, stiff, dry to moist (inferred alluvial deposits). | St | D-M | |
| 6 | | | | | | | |
| 6 | | | | | | | |
| 6 | | | | | | | |
| 6 | | | | | | | |
| 6 | | | | | | | |
| 7 | 1.5 | | CI | As above, orange grey, moist. | VSt-H | M | 1879-S8 |
| 9 | | | | | | | |
| 11 | | | | | | | |
| TP05 Terminated at 1.5m | | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




GroundScience

 (03) 5282 1566
 10 Dowsett St.
 South Geelong, Victoria 3220
 admin@groundscience.com.au

| | | | |
|--------------------------|------------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMEC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP05 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S8
Date Sampled: 16/05/2023
Dates Tested: 24/05/2023 - 08/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP05, Depth: 0.55m - 1.2m
Material: CI - sandy CLAY, orange mottled brown, medium plasticity, sand 36% fine to coarse grained, stiff, dry to moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing




Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| Particle Size Distribution (AS1289 3.6.1) | | | | |
|---|----------|----------------|------------|-----------------|
| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
| 4.75 mm | 100 | | 0 | |
| 2.36 mm | 100 | | 0 | |
| 1.18 mm | 99 | | 1 | |
| 0.6 mm | 96 | | 4 | |
| 0.425 mm | 91 | | 4 | |
| 0.3 mm | 85 | | 6 | |
| 0.15 mm | 78 | | 8 | |
| 0.075 mm | 64 | | 14 | |

| Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1) | | Min | Max |
|--|------------|-----|-----|
| Sample History | Oven Dried | | |
| Preparation Method | Dry Sieve | | |
| Liquid Limit (%) | 36 | | |
| Plastic Limit (%) | 14 | | |
| Plasticity Index (%) | 22 | | |

| Linear Shrinkage (AS1289 3.4.1) | | Min | Max |
|----------------------------------|---------------|-----|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | | |
| Linear Shrinkage (%) | 8.0 | | |
| Cracking Crumbling Curling | Cracking | | |



Material Test Report

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S8
Date Sampled: 16/05/2023
Dates Tested: 24/05/2023 - 19/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP05, Depth: 0.55m - 1.2m
Material: Cl - sandy CLAY, orange mottled brown, medium plasticity, sand 36% fine to coarse grained, stiff, dry to moist (inferred alluvial deposits).



Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au



Accredited for compliance with ISO/IEC 17025 - Testing




Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| California Bearing Ratio (AS 1289 6.1.1 & 2.1.1) | | Min | Max |
|--|-----------------------|-----|-----|
| CBR taken at | 2.5 mm | | |
| CBR % | 3.5 | | |
| Method of Compactive Effort | Standard | | |
| Method used to Determine MDD | AS 1289 5.1.1 & 2.1.1 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Maximum Dry Density (t/m ³) | 1.70 | | |
| Optimum Moisture Content (%) | 20.0 | | |
| Laboratory Density Ratio (%) | 98.5 | | |
| Laboratory Moisture Ratio (%) | 99.5 | | |
| Dry Density after Soaking (t/m ³) | 1.65 | | |
| Field Moisture Content (%) | | | |
| Moisture Content at Placement (%) | 19.7 | | |
| Moisture Content Top 30mm (%) | 21.9 | | |
| Moisture Content Rest of Sample (%) | 20.1 | | |
| Mass Surcharge (kg) | 4.5 | | |
| Soaking Period (days) | 4 | | |
| Curing Hours | 380.0 | | |
| Swell (%) | 1.0 | | |
| Oversize Material (mm) | 19 | | |
| Oversize Material Included | Excluded | | |
| Oversize Material (%) | 0.0 | | |
| Sample remoulded as per Vic Roads Code of Practice RC 500.16 | | | |

| Dry Density - Moisture Relationship (AS 1289 5.1.1 & 2.1.1) | | Min | Max |
|---|-------------------|-----|-----|
| Mould Type | 1 LITRE MOULD A | | |
| Compaction | Standard | | |
| Maximum Dry Density (t/m ³) | 1.70 | | |
| Optimum Moisture Content (%) | 20.0 | | |
| Oversize Sieve (mm) | 19.0 | | |
| Oversize Material Wet (%) | 0 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Curing Hours (h) | 238.2 | | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566

Engineering Log - Testpit

Testpit No: TP06

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.880564 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.620106 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.5m | Reviewed By : | Location : FORGE CREEK |
| | Date : 16/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-----------|-----------|-------------|---------------------|--|-------------|----------|---------|
| | | | | | | | |
| 2 | 0.3 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft to firm, moist, organics. | S-F | M | |
| 1 | | | | | | | |
| 2 | | | | | | | |
| 2 | 0.5 | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, firm to stiff, moist (inferred alluvial deposits). | F-St | M | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 3 | | | | | | | |
| 3 | | | | | | | |
| 3 | | | | | | | |
| 4 | | | | | | | |
| 4 | 1.1 | | CI | CLAY, trace sand, orange mottled grey, medium plasticity, sand fine to medium grained, very stiff to hard, moist (inferred alluvial deposits). | VSt-H | M | |
| 11 | | | | | | | |
| 10 | | | | | | | |
| 9 | | | | | | | |
| 12 | 1.5 | | | | | | |
| | | | | TP06 Terminated at 1.5m | | | |
| | -2 | | | | | | |
| | -2.5 | | | | | | |
| | 0 | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




GroundScience


 (03) 5282 1566

 10 Dowsett St.
South Geelong, Victoria 3220

 admin@groundscience.com.au

| | | | |
|--------------------------|-----------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP06 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566

Engineering Log - Testpit

Testpit No: TP07

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.880660 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.620384 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.5m | Reviewed By : | Location : FORGE CREEK |
| | Date : 16/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|---------------------------------|------------|-----------------------|---------------------|--|-------------|----------|-------------|
| | | | | | | | Bulk Sample |
| 2 1 2 1 | 0.4 | [Horizontal hatching] | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft to firm, moist, organics. | S-F | M | |
| 2 2 3 4 4 4 4 | 0.5 1.1 | [Diagonal hatching] | CH | CLAY, with sand, orange mottled brown, high plasticity, sand 23% fine to medium grained, firm to stiff, moist (inferred alluvial deposits). | F-St | M | |
| 7 9 9 8 | 1.1 1.5 | [Diagonal hatching] | CI | CLAY, trace sand, orange mottled grey, medium plasticity, sand fine to medium grained, very stiff, moist (inferred alluvial deposits). | VSt | M | 1879-S9 |
| TP07 Terminated at 1.5m | | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




GroundScience

(03) 5282 1566

10 Dowsett St.
South Geelong, Victoria 3220

admin@groundscience.com.au

| | | | |
|--------------------------|-----------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP07 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S9
Date Sampled: 16/05/2023
Dates Tested: 24/05/2023 - 08/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP07, Depth: 0.4m - 1.1m
Material: CH - CLAY, with sand, orange mottled brown, high plasticity, sand 23% fine to medium grained, firm to stiff, moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing




Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| Particle Size Distribution (AS1289 3.6.1) | | | | |
|---|----------|----------------|------------|-----------------|
| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
| 6.7 mm | 100 | | 0 | |
| 4.75 mm | 100 | | 0 | |
| 2.36 mm | 100 | | 0 | |
| 1.18 mm | 99 | | 0 | |
| 0.6 mm | 98 | | 2 | |
| 0.425 mm | 95 | | 3 | |
| 0.3 mm | 92 | | 3 | |
| 0.15 mm | 87 | | 5 | |
| 0.075 mm | 77 | | 10 | |

| Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1) | | | | Min | Max |
|--|------------|--|--|-----|-----|
| Sample History | Oven Dried | | | | |
| Preparation Method | Dry Sieve | | | | |
| Liquid Limit (%) | 53 | | | | |
| Plastic Limit (%) | 19 | | | | |
| Plasticity Index (%) | 34 | | | | |

| Linear Shrinkage (AS1289 3.4.1) | | | | Min | Max |
|----------------------------------|---------------|--|--|-----|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | | | | |
| Linear Shrinkage (%) | 10.0 | | | | |
| Cracking Crumbling Curling | Curling | | | | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S9
Date Sampled: 16/05/2023
Dates Tested: 24/05/2023 - 19/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP07, Depth: 0.4m - 1.1m
Material: CH - CLAY, with sand, orange mottled brown, high plasticity, sand 23% fine to medium grained, firm to stiff, moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au



Accredited for compliance with ISO/IEC 17025 - Testing




Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| California Bearing Ratio (AS 1289 6.1.1 & 2.1.1) | | Min | Max |
|--|-----------------------|-----|-----|
| CBR taken at | 2.5 mm | | |
| CBR % | 3.0 | | |
| Method of Compactive Effort | Standard | | |
| Method used to Determine MDD | AS 1289 5.1.1 & 2.1.1 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Maximum Dry Density (t/m ³) | 1.62 | | |
| Optimum Moisture Content (%) | 23.5 | | |
| Laboratory Density Ratio (%) | 98.0 | | |
| Laboratory Moisture Ratio (%) | 98.5 | | |
| Dry Density after Soaking (t/m ³) | 1.56 | | |
| Field Moisture Content (%) | | | |
| Moisture Content at Placement (%) | 23.2 | | |
| Moisture Content Top 30mm (%) | 27.6 | | |
| Moisture Content Rest of Sample (%) | 23.3 | | |
| Mass Surcharge (kg) | 4.5 | | |
| Soaking Period (days) | 4 | | |
| Curing Hours | 379.1 | | |
| Swell (%) | 2.0 | | |
| Oversize Material (mm) | 19 | | |
| Oversize Material Included | Excluded | | |
| Oversize Material (%) | 0.0 | | |
| Sample remoulded as per Vic Roads Code of Practice RC 500.16 | | | |

| Dry Density - Moisture Relationship (AS 1289 5.1.1 & 2.1.1) | | Min | Max |
|---|-------------------|-----|-----|
| Mould Type | 1 LITRE MOULD A | | |
| Compaction | Standard | | |
| Maximum Dry Density (t/m ³) | 1.62 | | |
| Optimum Moisture Content (%) | 23.5 | | |
| Oversize Sieve (mm) | 19.0 | | |
| Oversize Material Wet (%) | 0 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Curing Hours (h) | 236.2 | | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566

Engineering Log Testpit

Testpit No: TP08

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.880676 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.620646 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.5m | Reviewed By : | Location : FORGE CREEK |
| | Date : 16/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-----------|-----------|-------------|---------------------|---|-------------|----------|---------|
| | | | | | | | |
| 2 | 0.3 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, firm to stiff, moist, organics. | F-St | M | |
| 3 | | | | | | | |
| 4 | | | | | | | |
| 5 | 0.5 | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, stiff, moist (inferred alluvial deposits). | St | M | |
| 5 | | | | | | | |
| 6 | | | | | | | |
| 5 | | | | | | | |
| 5 | | | | | | | |
| 6 | 1.02 | | CI | CLAY, trace sand, orange mottled grey, medium plasticity, sand fine to medium grained, hard, dry to moist (inferred alluvial deposits). | H | D-M | |
| 10 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 18 | 1.5 | | | | | | |
| 20 | | | | | | | |
| R | 1.5 | | | TP08 Terminated at 1.5m | | | |
| | 2 | | | | | | |
| | 2.5 | | | | | | |
| | 3 | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




 (03) 5282 1566
 10 Dowsett St.
 South Geelong, Victoria 3220
 admin@groundscience.com.au

| | | | |
|--------------------------|------------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMEC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP08 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566

Engineering Log - Testpit

Testpit No: TP09

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.880903 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.619857 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.5m | Reviewed By : | Location : FORGE CREEK |
| | Date : 16/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-----------|-----------|-------------|---------------------|--|-------------|----------|-------------|
| | | | | | | | Bulk Sample |
| 2 | 0.35 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft to firm, moist, organics. | S-F | M | |
| 1 | | | | | | | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 1 | 0.5 | | CH | sandy CLAY, orange mottled brown, high plasticity, sand 36% fine to medium grained, firm to stiff, moist (inferred alluvial deposits). | F-St | M | |
| 1 | | | | | | | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 3 | | | | | | | |
| 3 | | | | | | | |
| 3 | | | | | | | |
| 4 | | | | | | | |
| 4 | | | | | | | |
| 5 | 1.3 | | CI | CLAY, trace sand, orange mottled grey, medium plasticity, sand fine to medium grained, stiff, dry to moist (inferred alluvial deposits). | St | D-M | 1879-S10 |
| 6 | | | | | | | |
| | 1.5 | | | TP09 Terminated at 1.5m | | | |
| | 2 | | | | | | |
| | 2.5 | | | | | | |
| | 3 | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




 (03) 5282 1566
 10 Dowsett St.
 South Geelong, Victoria 3220
 admin@groundscience.com.au

| | | | |
|--------------------------|-----------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP09 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S10
Date Sampled: 16/05/2023
Dates Tested: 24/05/2023 - 06/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP09, Depth: 0.35m - 1.3m
Material: CH - sandy CLAY, orange mottled brown, high plasticity, sand 36% fine to medium grained, firm to stiff, moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing




Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| Particle Size Distribution (AS1289 3.6.1) | | | | |
|---|----------|----------------|------------|-----------------|
| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
| 4.75 mm | 100 | | 0 | |
| 2.36 mm | 100 | | 0 | |
| 1.18 mm | 99 | | 0 | |
| 0.6 mm | 97 | | 3 | |
| 0.425 mm | 93 | | 4 | |
| 0.3 mm | 87 | | 5 | |
| 0.15 mm | 78 | | 9 | |
| 0.075 mm | 65 | | 13 | |

| Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1) | | | Min | Max |
|--|------------|--|-----|-----|
| Sample History | Oven Dried | | | |
| Preparation Method | Dry Sieve | | | |
| Liquid Limit (%) | 56 | | | |
| Plastic Limit (%) | 19 | | | |
| Plasticity Index (%) | 37 | | | |

| Linear Shrinkage (AS1289 3.4.1) | | | Min | Max |
|----------------------------------|--------------------|--|-----|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | | | |
| Linear Shrinkage (%) | 12.0 | | | |
| Cracking Crumbling Curling | Cracking & Curling | | | |



Material Test Report

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S10
Date Sampled: 16/05/2023
Dates Tested: 24/05/2023 - 09/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP09, Depth: 0.35m - 1.3m
Material: CH - sandy CLAY, orange mottled brown, high plasticity, sand 36% fine to medium grained, firm to stiff, moist (inferred alluvial deposits).



Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au



Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| California Bearing Ratio (AS 1289 6.1.1 & 2.1.1) | | Min | Max |
|--|-----------------------|-----|-----|
| CBR taken at | 2.5 mm | | |
| CBR % | 2.5 | | |
| Method of Compactive Effort | Standard | | |
| Method used to Determine MDD | AS 1289 5.1.1 & 2.1.1 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Maximum Dry Density (t/m ³) | 1.63 | | |
| Optimum Moisture Content (%) | 22.0 | | |
| Laboratory Density Ratio (%) | 98.0 | | |
| Laboratory Moisture Ratio (%) | 99.5 | | |
| Dry Density after Soaking (t/m ³) | 1.57 | | |
| Field Moisture Content (%) | | | |
| Moisture Content at Placement (%) | 21.8 | | |
| Moisture Content Top 30mm (%) | 23.9 | | |
| Moisture Content Rest of Sample (%) | 21.8 | | |
| Mass Surcharge (kg) | 4.5 | | |
| Soaking Period (days) | 4 | | |
| Curing Hours | 147.7 | | |
| Swell (%) | 2.0 | | |
| Oversize Material (mm) | 19 | | |
| Oversize Material Included | Excluded | | |
| Oversize Material (%) | 0.0 | | |
| Sample remoulded as per Vic Roads Code of Practice RC 500.16 | | | |

| Dry Density - Moisture Relationship (AS 1289 5.1.1 & 2.1.1) | | Min | Max |
|---|-------------------|-----|-----|
| Mould Type | 1 LITRE MOULD A | | |
| Compaction | Standard | | |
| Maximum Dry Density (t/m ³) | 1.63 | | |
| Optimum Moisture Content (%) | 22.0 | | |
| Oversize Sieve (mm) | 19.0 | | |
| Oversize Material Wet (%) | 0 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Curing Hours (h) | 90.0 | | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566


Engineering Log - Testpit
Testpit No: TP10

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.881065 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.620418 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.7m | Reviewed By : | Location : FORGE CREEK |
| | Date : 17/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-----------|-----------|-------------|---------------------|--|-------------|----------|-------------|
| | | | | | | | Bulk Sample |
| 1 | 0.3 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft to firm, moist, organics. | S-F | M | |
| 2 | | | | | | | |
| 1 | | | | | | | |
| 2 | 0.5 | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, firm to stiff, moist (inferred alluvial deposits). | F-St | M | |
| 2 | | | | | | | |
| 4 | | | | | | | |
| 5 | | | | | | | |
| 10 | 1.5 | | CI | CLAY, with sand, orange mottled grey, medium plasticity, sand 25% fine to medium grained, very stiff to hard, dry to moist (inferred alluvial deposits). | VS-H | D-M | |
| 14 | | | | | | | |
| 8 | | | | | | | |
| 9 | | | | | | | |
| 7 | | | | | | | |
| 7 | | | | | | | |
| 7 | | | | | | | |
| 12 | | | | | | | |
| | 2 | | | | | | 1879-S11 |
| | | | | | | | |
| | 2.5 | | | | | | |
| | | | | | | | |
| | 3 | | | | | | |

TP10 refusal at 1.7m

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




GroundScience

(03) 5282 1566

10 Dowsett St.
South Geelong, Victoria 3220

admin@groundscience.com.au

| | | | |
|--------------------------|------------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMEC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP10 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S11
Date Sampled: 17/05/2023
Dates Tested: 24/05/2023 - 07/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP10, Depth: 0.7m - 1.7m
Material: CI - CLAY, with sand, orange mottled grey, medium plasticity, sand 25% fine to medium grained, very stiff to hard, dry to moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing




Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| Particle Size Distribution (AS1289 3.6.1) | | | | |
|---|----------|----------------|------------|-----------------|
| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
| 4.75 mm | 100 | | 0 | |
| 2.36 mm | 100 | | 0 | |
| 1.18 mm | 100 | | 0 | |
| 0.6 mm | 99 | | 1 | |
| 0.425 mm | 97 | | 2 | |
| 0.3 mm | 94 | | 3 | |
| 0.15 mm | 88 | | 6 | |
| 0.075 mm | 75 | | 14 | |

| Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1) | | Min | Max |
|--|------------|-----|-----|
| Sample History | Oven Dried | | |
| Preparation Method | Dry Sieve | | |
| Liquid Limit (%) | 48 | | |
| Plastic Limit (%) | 17 | | |
| Plasticity Index (%) | 31 | | |

| Linear Shrinkage (AS1289 3.4.1) | | Min | Max |
|----------------------------------|---------------|-----|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | | |
| Linear Shrinkage (%) | 9.0 | | |
| Cracking Crumbling Curling | Curling | | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.





Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566

Engineering Log - Testpit
Testpit No: TP11

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.881542 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.620354 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.5m | Reviewed By : | Location : FORGE CREEK |
| | Date : 17/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples | |
|-----------|-----------|-------------|---------------------|--|-------------|----------|---------|--|
| | | | | | | | | |
| 2 | 0.3 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft to firm, moist, organics. | S-F | M | | |
| 1 | | | | | | | | |
| 1 | | | | | | | | |
| 1 | 0.5 | | CH | CLAY, trace sand, orange mottled brown, high plasticity, sand fine to medium grained, soft to firm, moist (inferred alluvial deposits). | S-F | M | | |
| 1 | | | | | | | | |
| 1 | | | | | | | | |
| 1 | | | | | | | | |
| 1 | | | | | | | | |
| 2 | | | | | | | | |
| 2 | | | | | | | | |
| 3 | 0.9 | | CH | As above, stiff. | St | M | | |
| 3 | | | | | | | | |
| 3 | | | | | | | | |
| 5 | | | | | | | | |
| 5 | | | | | | | | |
| 5 | 1.5 | | | | | | | |
| 5 | | | | | | | | |
| 5 | | | | | | | | |
| | 1.5 | | | TP11 Terminated at 1.5m | | | | |
| | 2 | | | | | | | |
| | 2.5 | | | | | | | |
| | 3 | | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




GroundScience

(03) 5282 1566

10 Dowsett St.
South Geelong, Victoria 3220

admin@groundscience.com.au

| | | | |
|--------------------------|------------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMEC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP11 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566


Engineering Log - Testpit

Testpit No: TP 12

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.882014 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.620238 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.7m | Reviewed By : | Location : FORGE CREEK |
| | Date : 17/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples | |
|-----------|-----------|-------------|---|--|-------------|----------|-------------|----------|
| | | | | | | | Bulk Sample | |
| 1 | 0.3 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft to firm, moist, organics. | S-F | M | | |
| 1 | | | | | | | | |
| 2 | | | | | | | | |
| 4 | 0.5 | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, stiff, moist (inferred alluvial deposits). | St | M | | |
| 5 | | | | | | | | |
| 6 | | | | | | | | |
| 4 | | | | | | | | |
| 5 | | | | | | | | |
| 3 | | | | | | | | |
| 3 | 1 | | CI | CLAY, trace sand, orange mottled grey, medium plasticity, sand fine to medium grained, stiff, dry to moist (inferred alluvial deposits). | St | M-D | | |
| 3 | | | | | | | | |
| 3 | | | | | | | | |
| 3 | | | | | | | | |
| 5 | | | | | | | | |
| | 1.5 | | CH | CLAY, trace sand & gravel, orange mottled red/grey, high plasticity, sand 15% fine to medium grained, gravel 8% fine to medium, stiff to very stiff, moist (inferred alluvial deposits). | St-VSt | M | | |
| | 2 | | TP12 refusal at 1.7m (Refusal on Rock) | | | | | 1879-S12 |
| | 2.5 | | | | | | | |
| | 3 | | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




GroundScience

(03) 5282 1566

10 Dowsett St.
South Geelong, Victoria 3220

admin@groundscience.com.au

| | | | |
|--------------------------|------------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMEC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP12 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S12
Date Sampled: 17/05/2023
Dates Tested: 24/05/2023 - 08/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP12, Depth: 1.5m - 1.7m
Material: CH - CLAY, trace sand & gravel, orange mottled red/grey, high plasticity, sand 15% fine to medium grained, gravel 8% fine to medium, stiff to very stiff, moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing




Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| Particle Size Distribution (AS1289 3.6.1) | | | | |
|---|----------|----------------|------------|-----------------|
| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
| 26.5 mm | 100 | | 0 | |
| 19 mm | 97 | | 3 | |
| 13.2 mm | 94 | | 2 | |
| 9.5 mm | 94 | | 0 | |
| 6.7 mm | 94 | | 1 | |
| 4.75 mm | 93 | | 0 | |
| 2.36 mm | 92 | | 1 | |
| 1.18 mm | 92 | | 1 | |
| 0.6 mm | 90 | | 1 | |
| 0.425 mm | 88 | | 2 | |
| 0.3 mm | 85 | | 3 | |
| 0.15 mm | 82 | | 3 | |
| 0.075 mm | 77 | | 5 | |

| Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1) | | Min | Max |
|--|------------|-----|-----|
| Sample History | Oven Dried | | |
| Preparation Method | Dry Sieve | | |
| Liquid Limit (%) | 58 | | |
| Plastic Limit (%) | 15 | | |
| Plasticity Index (%) | 43 | | |

| Linear Shrinkage (AS1289 3.4.1) | | Min | Max |
|----------------------------------|--------------------|-----|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | | |
| Linear Shrinkage (%) | 10.5 | | |
| Cracking Crumbling Curling | Cracking & Curling | | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.

| DCP graph | | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-------------------------|--|-----------|-------------|---------------------|---|-------------|----------|-------------|
| | | | | | | | | Bulk Sample |
| 1 | | 0.3 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, firm to stiff, moist, organics. | F-St | M | |
| 2 | | | | | | | | |
| 4 | | | | | | | | |
| 7 | | 0.5 | | CI | CLAY, with sand, orange mottled brown, medium plasticity, sand 23% fine to medium grained, very stiff to hard, moist (inferred alluvial deposits). | VSt-H | M | |
| 8 | | | | | | | | |
| 7 | | | | | | | | |
| 7 | | | | | | | | |
| 7 | | | | | | | | |
| 6 | | | | | | | | |
| 7 | | | | | | | | |
| 7 | | | | | | | | |
| 9 | | | | | | | | |
| 8 | | | | | | | | |
| 9 | | 1 | | | | | | |
| 10 | | | | | | | | |
| TP13 Terminated at 1.5m | | | | | | | | 1879-S13 |
| | | 1.5 | | | | | | |
| | | 2 | | | | | | |
| | | 2.5 | | | | | | |
| | | 3 | | | | | | |

Engineering Log Testpit

Testpit No: TP13

Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.882501 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.620134 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.5m | Reviewed By : | Location : FORGE CREEK |
| | Date : 17/05/2023 | Loc Comment : |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




GroundScience

(03) 5282 1566

10 Dowsett St.
South Geelong, Victoria 3220

admin@groundscience.com.au

| | | | |
|--------------------------|------------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMEC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP13 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S13
Date Sampled: 17/05/2023
Dates Tested: 24/05/2023 - 06/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP13, Depth: 0.3m - 1.5m
Material: CI - CLAY, with sand, orange mottled brown, medium plasticity, sand 23% fine to medium grained, very stiff to hard, moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing




Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| Particle Size Distribution (AS1289 3.6.1) | | | | |
|---|----------|----------------|------------|-----------------|
| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
| 4.75 mm | 100 | | 0 | |
| 2.36 mm | 100 | | 0 | |
| 1.18 mm | 100 | | 0 | |
| 0.6 mm | 98 | | 2 | |
| 0.425 mm | 95 | | 3 | |
| 0.3 mm | 91 | | 4 | |
| 0.15 mm | 85 | | 6 | |
| 0.075 mm | 77 | | 8 | |

| Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1) | | Min | Max |
|--|------------|-----|-----|
| Sample History | Oven Dried | | |
| Preparation Method | Dry Sieve | | |
| Liquid Limit (%) | 50 | | |
| Plastic Limit (%) | 17 | | |
| Plasticity Index (%) | 33 | | |

| Linear Shrinkage (AS1289 3.4.1) | | Min | Max |
|----------------------------------|--------------------|-----|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | | |
| Linear Shrinkage (%) | 11.0 | | |
| Cracking Crumbling Curling | Cracking & Curling | | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S13
Date Sampled: 17/05/2023
Dates Tested: 24/05/2023 - 19/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP13, Depth: 0.3m - 1.5m
Material: Cl - CLAY, with sand, orange mottled brown, medium plasticity, sand 23% fine to medium grained, very stiff to hard, moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au



Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| California Bearing Ratio (AS 1289 6.1.1 & 2.1.1) | | Min | Max |
|--|-----------------------|-----|-----|
| CBR taken at | 2.5 mm | | |
| CBR % | 3.5 | | |
| Method of Compactive Effort | Standard | | |
| Method used to Determine MDD | AS 1289 5.1.1 & 2.1.1 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Maximum Dry Density (t/m ³) | 1.61 | | |
| Optimum Moisture Content (%) | 22.5 | | |
| Laboratory Density Ratio (%) | 98.0 | | |
| Laboratory Moisture Ratio (%) | 100.5 | | |
| Dry Density after Soaking (t/m ³) | 1.56 | | |
| Field Moisture Content (%) | | | |
| Moisture Content at Placement (%) | 22.9 | | |
| Moisture Content Top 30mm (%) | 26.8 | | |
| Moisture Content Rest of Sample (%) | 24.0 | | |
| Mass Surcharge (kg) | 4.5 | | |
| Soaking Period (days) | 4 | | |
| Curing Hours | 377.6 | | |
| Swell (%) | 1.0 | | |
| Oversize Material (mm) | 19 | | |
| Oversize Material Included | Excluded | | |
| Oversize Material (%) | 0.0 | | |
| Sample remoulded as per Vic Roads Code of Practice RC 500.16 | | | |

| Dry Density - Moisture Relationship (AS 1289 5.1.1 & 2.1.1) | | Min | Max |
|---|-------------------|-----|-----|
| Mould Type | 1 LITRE MOULD A | | |
| Compaction | Standard | | |
| Maximum Dry Density (t/m ³) | 1.61 | | |
| Optimum Moisture Content (%) | 22.5 | | |
| Oversize Sieve (mm) | 19.0 | | |
| Oversize Material Wet (%) | 0 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Curing Hours (h) | 211.6 | | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566

Engineering Log - Testpit

Testpit No: TP14

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.882951 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.620041 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.63m | Reviewed By : | Location : FORGE CREEK |
| | Date : 17/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-----------|-----------|-------------|---------------------|---|-------------|----------|-------------|
| | | | | | | | Bulk Sample |
| 2 | 0.3 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, firm to stiff, dry to moist, organics. | F-St | D-M | |
| 2 | | | | | | | |
| 4 | | | | | | | |
| 4 | 0.5 | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, stiff, moist (inferred alluvial deposits). | St | M | |
| 4 | | | | | | | |
| 4 | | | | | | | |
| 4 | | | | | | | |
| 4 | | | | | | | |
| 5 | | | | | | | |
| 5 | 1 | | CL | sandy CLAY, trace gravel, orange mottled grey, low plasticity, sand 40% fine to coarse grained, gravel 2%, stiff, moist (inferred alluvial deposits). | St | M | |
| 6 | | | | | | | |
| 5 | | | | | | | |
| 5 | | | | | | | |
| 6 | | | | | | | |
| | 1.5 | | | | | | |
| | 1.6 | | CH | CLAY, with sand & gravel, grey mottled orange/red, high plasticity, sand fine to coarse grained, gravel sub angular medium to coarse, hard, dry (inferred Haunted Hills Formation residual soil). | H | D | 1879 S14 |
| | | | | TP14 refusal at 1.63m | | | |
| | 2 | | | | | | |
| | 2.5 | | | | | | |
| | 3 | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




GroundScience

(03) 5282 1566

10 Dowsett St.
South Geelong, Victoria 3220

admin@groundscience.com.au

| | | | |
|--------------------------|-----------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP14 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S14
Date Sampled: 17/05/2023
Dates Tested: 24/05/2023 - 07/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP14, Depth: 1.0m - 1.6m
Material: CL - sandy CLAY, trace gravel, orange mottled grey, low plasticity, sand 40% fine to coarse grained, gravel 2%, stiff, moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

Particle Size Distribution (AS1289 3.6.1)


| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
|----------|----------|----------------|------------|-----------------|
| 19 mm | 100 | | 0 | |
| 13.2 mm | 100 | | 0 | |
| 9.5 mm | 99 | | 1 | |
| 6.7 mm | 99 | | 0 | |
| 4.75 mm | 99 | | 0 | |
| 2.36 mm | 98 | | 0 | |
| 1.18 mm | 97 | | 1 | |
| 0.6 mm | 94 | | 4 | |
| 0.425 mm | 89 | | 5 | |
| 0.3 mm | 83 | | 6 | |
| 0.15 mm | 72 | | 10 | |
| 0.075 mm | 58 | | 14 | |

Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1)


| | Min | Max |
|----------------------|------------|-----|
| Sample History | Oven Dried | |
| Preparation Method | Dry Sieve | |
| Liquid Limit (%) | 34 | |
| Plastic Limit (%) | 13 | |
| Plasticity Index (%) | 21 | |

Linear Shrinkage (AS1289 3.4.1)

| | Min | Max |
|----------------------------------|----------------------|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | |
| Linear Shrinkage (%) | 7.0 | |
| Cracking Crumbling Curling | Cracking & Crumbling | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566



Engineering Log - Testpit

Testpit No: TP15

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.883409 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.619978 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.25m | Reviewed By : | Location : FORGE CREEK |
| | Date : 17/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-----------|-----------|-------------|---------------------|---|-------------|----------|-------------|
| | | | | | | | Bulk Sample |
| 2 | 0.25 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft to firm, dry to moist, organics. | S-F | D-M | |
| 1 | | | | | | | |
| 2 | 0.5 | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, stiff, dry to moist (inferred alluvial deposits). | St | D-M | |
| 2 | | | | | | | |
| 3 | | | | | | | |
| 4 | | | | | | | |
| 6 | 1 | | CI | sandy CLAY, trace gravel, orange mottled red/grey, medium plasticity, sand 45% fine to coarse grained, gravel 1%, very stiff to hard, dry (inferred Haunted Hills Formation residual soil). | VSt-H | D | |
| 7 | | | | | | | |
| 9 | | | | | | | |
| 13 | | | | | | | |
| 16 | | | | | | | |
| 20 | | | | | | | |
| R | | | | | | | |
| | | | | TP15 refusal at 1.25m | | | 1879-S15 |
| | 1.5 | | | | | | |
| | 2 | | | | | | |
| | 2.5 | | | | | | |
| | 3 | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




GroundScience

(03) 5282 1566

10 Dowsett St.
South Geelong, Victoria 3220

admin@groundscience.com.au

| | | | |
|--------------------------|-----------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP15 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S15
Date Sampled: 17/05/2023
Dates Tested: 24/05/2023 - 07/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP15, Depth: 0.6m - 1.25m
Material: CI - sandy CLAY, trace gravel, orange mottled red/grey, medium plasticity, sand 45% fine to coarse grained, gravel 1%, very stiff to hard, dry (Inferred Haunted Hills Formation residual soil).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing




Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| Particle Size Distribution (AS1289 3.6.1) | | | | |
|---|----------|----------------|------------|-----------------|
| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
| 19 mm | 100 | | 0 | |
| 13.2 mm | 100 | | 0 | |
| 9.5 mm | 100 | | 0 | |
| 6.7 mm | 100 | | 0 | |
| 4.75 mm | 99 | | 0 | |
| 2.36 mm | 99 | | 0 | |
| 1.18 mm | 98 | | 1 | |
| 0.6 mm | 95 | | 4 | |
| 0.425 mm | 90 | | 5 | |
| 0.3 mm | 84 | | 6 | |
| 0.15 mm | 73 | | 11 | |
| 0.075 mm | 54 | | 19 | |

| Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1) | | Min | Max |
|--|------------|-----|-----|
| Sample History | Oven Dried | | |
| Preparation Method | Dry Sieve | | |
| Liquid Limit (%) | 36 | | |
| Plastic Limit (%) | 12 | | |
| Plasticity Index (%) | 24 | | |

| Linear Shrinkage (AS1289 3.4.1) | | Min | Max |
|----------------------------------|----------------------|-----|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | | |
| Linear Shrinkage (%) | 7.0 | | |
| Cracking Crumbling Curling | Cracking & Crumbling | | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S15
Date Sampled: 17/05/2023
Dates Tested: 24/05/2023 - 19/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP15, Depth: 0.6m - 1.25m
Material: Cl - sandy CLAY, trace gravel, orange mottled red/grey, medium plasticity, sand 45% fine to coarse grained, gravel 1%, very stiff to hard, dry (Inferred Haunted Hills Formation residual soil).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au



Accredited for compliance with ISO/IEC 17025 - Testing




Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| California Bearing Ratio (AS 1289 6.1.1 & 2.1.1) | | Min | Max |
|--|-----------------------|-----|-----|
| CBR taken at | 2.5 mm | | |
| CBR % | 2.5 | | |
| Method of Compactive Effort | Standard | | |
| Method used to Determine MDD | AS 1289 5.1.1 & 2.1.1 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Maximum Dry Density (t/m ³) | 1.79 | | |
| Optimum Moisture Content (%) | 15.5 | | |
| Laboratory Density Ratio (%) | 98.0 | | |
| Laboratory Moisture Ratio (%) | 98.5 | | |
| Dry Density after Soaking (t/m ³) | 1.74 | | |
| Field Moisture Content (%) | | | |
| Moisture Content at Placement (%) | 15.2 | | |
| Moisture Content Top 30mm (%) | 19.3 | | |
| Moisture Content Rest of Sample (%) | 15.7 | | |
| Mass Surcharge (kg) | 4.5 | | |
| Soaking Period (days) | 4 | | |
| Curing Hours | 362.5 | | |
| Swell (%) | 1.5 | | |
| Oversize Material (mm) | 19 | | |
| Oversize Material Included | Excluded | | |
| Oversize Material (%) | 0.0 | | |
| Sample remoulded as per Vic Roads Code of Practice RC 500.16 | | | |

| Dry Density - Moisture Relationship (AS 1289 5.1.1 & 2.1.1) | | Min | Max |
|---|-------------------|-----|-----|
| Mould Type | 1 LITRE MOULD A | | |
| Compaction | Standard | | |
| Maximum Dry Density (t/m ³) | 1.79 | | |
| Optimum Moisture Content (%) | 15.5 | | |
| Oversize Sieve (mm) | 19.0 | | |
| Oversize Material Wet (%) | 0 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Curing Hours (h) | 176.4 | | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566

Engineering Log - Testpit

Testpit No: TP 16

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.883871 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.619890 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.5m | Reviewed By : | Location : FORGE CREEK |
| | Date : 17/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-------------------------|-----------|-------------|---------------------|--|-------------|----------|---------|
| | | | | | | | |
| 1 | 0.3 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft to firm, moist, organics. | S-F | M | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 2 | 0.5 | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, firm to stiff, moist (inferred alluvial deposits). | F-St | M | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 3 | | | | | | | |
| 3 | | | | | | | |
| 3 | 0.8 | | CI | CLAY, trace sand, orange mottled grey, medium plasticity, sand fine to medium grained, very to very stiff, dry (inferred alluvial deposits). | St-VSt | D | |
| 3 | | | | | | | |
| 4 | | | | | | | |
| 4 | | | | | | | |
| 4 | | | | | | | |
| 5 | | | | | | | |
| 7 | 1.5 | | | | | | |
| TP16 Terminated at 1.5m | | | | | | | |
| | 2 | | | | | | |
| | 2.5 | | | | | | |
| | 3 | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.






GroundScience

 (03) 5282 1566
 10 Dowsett St.
 South Geelong, Victoria 3220
 admin@groundscience.com.au

| | | | |
|--------------------------|------------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMEC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP16 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




GroundScience


(03) 5282 1566

10 Dowsett St.
South Geelong, Victoria 3220

admin@groundscience.com.au

| | | | |
|--------------------------|-----------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP17 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566

Engineering Log - Testpit



Testpit No: TP18

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.884153 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.619998 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.5m | Reviewed By : | Location : FORGE CREEK |
| | Date : 17/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-----------|-----------|-------------|---------------------|--|-------------|----------|---------|
| | | | | | | | |
| 1 | 0.4 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft to firm, moist, organics. | S-F | M | |
| 2 | | | | | | | |
| 3 | | | | | | | |
| 4 | | | | | | | |
| 5 | 0.5 | | CH | CLAY, trace sand and gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, stiff, moist (inferred alluvial deposits). | St | M | |
| 5 | | | | | | | |
| 5 | | | | | | | |
| 5 | | | | | | | |
| 5 | | | | | | | |
| 5 | | | | | | | |
| 5 | | | | | | | |
| 5 | | | | | | | |
| 5 | | | | | | | |
| 5 | | | | | | | |
| 4 | 1 | | | | | | |
| 5 | | | | | | | |
| 5 | 1.5 | | | | | | |
| 5 | | | | | | | |
| 5 | | | | | | | |
| | 2 | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | 2.5 | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | 3 | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | 3.5 | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | 4 | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | 4.5 | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | 5 | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | 5.5 | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | 6 | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | 6.5 | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | 7 | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | 7.5 | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | 8 | | | | | | |
| | | | | | | | |
| | | | | | | | |

TP18 Terminated at 1.5m

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




 (03) 5282 1566
 10 Dowsett St.
 South Geelong, Victoria 3220
 admin@groundscience.com.au

| | | | |
|--------------------------|------------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMEC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP18 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.

| DCP graph | | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples | |
|-----------|--|-----------|-------------|---------------------|---|-------------|----------|-------------|--|
| | | | | | | | | Bulk Sample | |
| 2 | | 0.2 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, firm, dry to moist, organics. | F | D-M | | |
| 2 | | | | CL | As above, fine to coarse sized gravel, stiff, moist. | St | M | | |
| 3 | | 0.4 | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, stiff, moist (inferred alluvial deposits). | St | M | | |
| 3 | | | | | | | | | |
| 3 | | | | | | | | | |
| 4 | | 0.7 | | CI | CLAY, trace sand, orange mottled grey, medium plasticity, sand 14% fine to medium grained, stiff to very stiff, moist (inferred alluvial deposits). | St-VSt | M | | |
| 3 | | | | | | | | | |
| 4 | | | | | | | | | |
| 5 | | | | | | | | | |
| 7 | | | | | | | | | |
| 7 | | 1.2 | | CH | CLAY, with sand & gravel, grey mottled orange/red, high plasticity, sand fine to coarse grained, gravel sub angular medium to coarse, hard, moist (inferred Haunted Hills Formation residual soil). | H | M | 1879-S16 | |
| 16 | | | | | | | | | |
| 20 | | | | | | | | | |
| R | | 1.5 | | | TP19 refusal at 1.4m | | | | |
| | | 2 | | | | | | | |
| | | 2.5 | | | | | | | |
| | | 3 | | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




GroundScience

 (03) 5282 1566
 10 Dowsett St.
 South Geelong, Victoria 3220
 admin@groundscience.com.au

| | | | |
|--------------------------|-----------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP19 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S16
Date Sampled: 18/05/2023
Dates Tested: 24/05/2023 - 13/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP19, Depth: 0.7m - 1.2m
Material: Cl - CLAY, trace sand, orange mottled grey, medium plasticity, sand
 14% fine to medium grained, hard, moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing




Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109


| Particle Size Distribution (AS1289 3.6.1) | | | | |
|---|----------|----------------|------------|-----------------|
| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
| 6.7 mm | 100 | | 0 | |
| 4.75 mm | 100 | | 0 | |
| 2.36 mm | 100 | | 0 | |
| 1.18 mm | 99 | | 1 | |
| 0.6 mm | 97 | | 1 | |
| 0.425 mm | 96 | | 1 | |
| 0.3 mm | 95 | | 1 | |
| 0.15 mm | 93 | | 2 | |
| 0.075 mm | 86 | | 7 | |

| Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1) | | | | Min | Max |
|--|------------|--|--|-----|-----|
| Sample History | Oven Dried | | | | |
| Preparation Method | Dry Sieve | | | | |
| Liquid Limit (%) | 41 | | | | |
| Plastic Limit (%) | 17 | | | | |
| Plasticity Index (%) | 24 | | | | |

| Linear Shrinkage (AS1289 3.4.1) | | | | Min | Max |
|----------------------------------|--------------------|--|--|-----|-----|
| Moisture Condition Determined By | AS 1289.3.1.1 | | | | |
| Linear Shrinkage (%) | 8.5 | | | | |
| Cracking Crumbling Curling | Cracking & Curling | | | | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566


Engineering Log - Testpit

Testpit No: TP20

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.884674 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.618974 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.5m | Reviewed By : | Location : FORGE CREEK |
| | Date : 18/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-----------|-----------|-------------|---------------------|---|-------------|----------|-------------|
| | | | | | | | Bulk Sample |
| 1 | 0.2 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft to firm, dry to moist, organics. | S-F | D-M | |
| 2 | | | CL | As above, grey brown, fine to coarse sized gravel, moist. | S-F | M | |
| 2 | 0.4 | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, firm to stiff, moist (inferred alluvial deposits). | F-St | M | |
| 3 | | | | | | | |
| 3 | | | | | | | |
| 4 | | | | | | | |
| 4 | | | | | | | |
| 3 | | | | | | | |
| 1 | | | | | | | |
| 3 | | | | | | | |
| 4 | 1.2 | | CH | CLAY, with sand & gravel, grey mottled orange/red, high plasticity, sand 20% fine to coarse grained, gravel 18% medium to coarse, hard, moist (inferred Haunted Hills Formation residual soil). | H | M | |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 14 | 1.5 | | | | | | 1879-S17 |
| | | | | TP20 Terminated at 1.5m | | | |
| | -2 | | | | | | |
| | -2.5 | | | | | | |
| | 0 | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




GroundScience

(03) 5282 1566

10 Dowsett St.
South Geelong, Victoria 3220

admin@groundscience.com.au

| | | | |
|--------------------------|-----------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP20 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S17
Date Sampled: 18/05/2023
Dates Tested: 24/05/2023 - 07/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP20, Depth: 1.2m - 1.5m
Material: CH - CLAY, with sand & gravel, grey mottled orange/red, high plasticity, sand 20% fine to coarse grained, gravel 18% medium to coarse, hard, moist (inferred Haunted Hills Formation residual soil).


Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109


| Particle Size Distribution (AS1289 3.6.1) | | | | |
|---|----------|----------------|------------|-----------------|
| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
| 75 mm | 100 | | 0 | |
| 63 mm | 97 | | 3 | |
| 53 mm | 97 | | 0 | |
| 37.5 mm | 95 | | 1 | |
| 26.5 mm | 93 | | 3 | |
| 19 mm | 92 | | 1 | |
| 13.2 mm | 91 | | 1 | |
| 9.5 mm | 88 | | 3 | |
| 6.7 mm | 85 | | 2 | |
| 4.75 mm | 84 | | 1 | |
| 2.36 mm | 82 | | 2 | |
| 1.18 mm | 78 | | 3 | |
| 0.6 mm | 73 | | 5 | |
| 0.425 mm | 71 | | 2 | |
| 0.3 mm | 69 | | 2 | |
| 0.15 mm | 67 | | 2 | |
| 0.075 mm | 62 | | 5 | |



| Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1) | | Min | Max |
|--|------------|-----|-----|
| Sample History | Oven Dried | | |
| Preparation Method | Dry Sieve | | |
| Liquid Limit (%) | 96 | | |
| Plastic Limit (%) | 26 | | |
| Plasticity Index (%) | 70 | | |

| Linear Shrinkage (AS1289 3.4.1) | | Min | Max |
|----------------------------------|--------------------|-----|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | | |
| Linear Shrinkage (%) | 14.5 | | |
| Cracking Crumbling Curling | Cracking & Curling | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566


Engineering Log - Testpit

Testpit No: TP21

| | | |
|--------------------------|---|---------------------------------|
| Latitude : -37.884814 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.619825 | Excavator Supplier : Supplied By Client | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.5m | Reviewed By : | Location : FORGE CREEK |
| | Date : 18/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-------------------------|-----------|-------------|---------------------|--|-------------|----------|---------|
| | | | | | | | |
| 1 | 0.2 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft, moist, organics. | S | M | |
| 3 | | | CL | As above, gravel fine to coarse, stiff. | St | M | |
| 3 | 0.5 | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, stiff, moist (inferred alluvial deposits). | St | M | |
| 5 | | | | | | | |
| 4 | | | | | | | |
| 4 | 1.5 | | CI | CLAY, trace sand, orange mottled grey, medium plasticity, sand fine to medium grained, stiff, moist (inferred alluvial deposits). | St | M-D | |
| 4 | | | | | | | |
| 3 | | | | | | | |
| 3 | | | | | | | |
| 4 | | | | | | | |
| 4 | | | | | | | |
| 4 | | | | | | | |
| TP21 Terminated at 1.5m | | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.





GroundScience

 (03) 5282 1566
 10 Dowsett St.
 South Geelong, Victoria 3220
 admin@groundscience.com.au

| | | | |
|--------------------------|------------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMEC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP21 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566



Engineering Log - Testpit

Testpit No: TP22

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.885153 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.618866 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.5m | Reviewed By : | Location : FORGE CREEK |
| | Date : 18/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-------------------------|-----------|-------------|---------------------|--|-------------|----------|---------|
| | | | | | | | |
| 1 | 0.2 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft to firm, moist, organics. | S-F | M | |
| 2 | | | CL | As above, grey brown, fine to coarse sized gravel, firm to stiff, dry to moist. | F-St | D-M | |
| 3 | 0.4 | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, stiff, moist (inferred alluvial deposits). | St | M | |
| 4 | | | | | | | |
| 5 | 0.8 | | CH | CLAY, with sand & gravel, grey mottled orange/red, high plasticity, sand fine to coarse grained, gravel sub angular medium to coarse, stiff, moist (inferred Haunted Hills Formation residual soil). | St | M | |
| 4 | | | | | | | |
| 4 | 1.0 | | | | | | |
| 4 | | | | | | | |
| 5 | 1.5 | | | | | | |
| 6 | | | | | | | |
| TP22 Terminated at 1.5m | | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




GroundScience

 (03) 5282 1566
 10 Dowsett St.
 South Geelong, Victoria 3220
 admin@groundscience.com.au

| | | | |
|--------------------------|------------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMEC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP22 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




GroundScience

(03) 5282 1566

10 Dowsett St.
South Geelong, Victoria 3220

admin@groundscience.com.au

| | | | |
|--------------------------|-----------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP23 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S18
Date Sampled: 19/05/2023
Dates Tested: 24/05/2023 - 08/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP23, Depth: 0.4m - 1.5m
Material: CH - CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand 13% fine to coarse grained, gravel 2%, stiff, moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

Particle Size Distribution (AS1289 3.6.1)


| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
|----------|----------|----------------|------------|-----------------|
| 19 mm | 100 | | 0 | |
| 13.2 mm | 100 | | 0 | |
| 9.5 mm | 99 | | 1 | |
| 6.7 mm | 99 | | 0 | |
| 4.75 mm | 98 | | 0 | |
| 2.36 mm | 98 | | 1 | |
| 1.18 mm | 96 | | 2 | |
| 0.6 mm | 94 | | 2 | |
| 0.425 mm | 92 | | 2 | |
| 0.3 mm | 91 | | 1 | |
| 0.15 mm | 89 | | 2 | |
| 0.075 mm | 85 | | 4 | |

Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1)


| | Min | Max |
|----------------------|------------|-----|
| Sample History | Oven Dried | |
| Preparation Method | Dry Sieve | |
| Liquid Limit (%) | 88 | |
| Plastic Limit (%) | 27 | |
| Plasticity Index (%) | 61 | |

Linear Shrinkage (AS1289 3.4.1)

| | Min | Max |
|----------------------------------|--------------------|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | |
| Linear Shrinkage (%) | 12.5 | |
| Cracking Crumbling Curling | Cracking & Curling | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566



Engineering Log - Testpit

Testpit No: TP24

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.885511 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.619229 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.5m | Reviewed By : | Location : FORGE CREEK |
| | Date : 19/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-----------|-----------|-------------|---------------------|---|-------------|----------|-------------|
| | | | | | | | Bulk Sample |
| 1 | 0.2 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft, moist, organics. | S | M | |
| 2 | | | CL | As above, grey brown, fine to coarse sized gravel, firm to stiff. | F-St | M | |
| 5 | 0.5 | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand 14% fine to coarse grained, gravel 9% fine to medium, stiff, moist (inferred alluvial deposits). | St | M | |
| 3 | | | | | | | |
| 6 | | | | | | | |
| 6 | | | | | | | |
| 6 | | | | | | | |
| 7 | 1.1 | | CH | CLAY, with sand & gravel, grey mottled orange/red, high plasticity, sand fine to coarse grained, gravel sub angular medium to coarse, very stiff to hard, moist (inferred Haunted Hills Formation residual soil). | VSt-H | M | 1879-S19 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 14 | | | | | | | |
| | 1.5 | | | TP24 Terminated at 1.5m | | | |
| | 2 | | | | | | |
| | 2.5 | | | | | | |
| | 3 | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




 (03) 5282 1566
 10 Dowsett St.
 South Geelong, Victoria 3220
 admin@groundscience.com.au

| | | | |
|--------------------------|------------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMEC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP24 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S19
Date Sampled: 19/05/2023
Dates Tested: 24/05/2023 - 13/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP24, Depth: 0.4m - 1.1m
Material: CH - CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand 14% fine to coarse grained, gravel 9% fine to medium, stiff, moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing




Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109


| Particle Size Distribution (AS1289 3.6.1) | | | | |
|---|----------|----------------|------------|-----------------|
| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
| 37.5 mm | 100 | | 0 | |
| 26.5 mm | 99 | | 1 | |
| 19 mm | 99 | | 0 | |
| 13.2 mm | 99 | | 0 | |
| 9.5 mm | 97 | | 2 | |
| 6.7 mm | 94 | | 3 | |
| 4.75 mm | 92 | | 1 | |
| 2.36 mm | 91 | | 2 | |
| 1.18 mm | 89 | | 2 | |
| 0.6 mm | 86 | | 3 | |
| 0.425 mm | 85 | | 2 | |
| 0.3 mm | 83 | | 1 | |
| 0.15 mm | 81 | | 2 | |
| 0.075 mm | 77 | | 4 | |

| Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1) | | Min | Max |
|--|------------|-----|-----|
| Sample History | Oven Dried | | |
| Preparation Method | Dry Sieve | | |
| Liquid Limit (%) | 78 | | |
| Plastic Limit (%) | 47 | | |
| Plasticity Index (%) | 31 | | |

| Linear Shrinkage (AS1289 3.4.1) | | Min | Max |
|----------------------------------|--------------------|-----|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | | |
| Linear Shrinkage (%) | 14.0 | | |
| Cracking Crumbling Curling | Cracking & Curling | | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566




Engineering Log - Testpit

Testpit No: TP25

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.885764 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.618692 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.5m | Reviewed By : | Location : FORGE CREEK |
| | Date : 19/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-----------|-----------|-------------|---------------------|---|-------------|----------|-------------|
| | | | | | | | Bulk Sample |
| 1 | 0.2 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft, moist, organics. | S | M | |
| 1 | | | | | | | |
| 4 | 0.3 | | CL | As above, grey brown, gravel fine to coarse, stiff. | St | M | |
| 3 | | | | | | | |
| 4 | 0.5 | | CH | Natural CLAY, with fine to coarse grained sand, trace fine sized gravel, orange brown, high plasticity, stiff, moist. | St | M | |
| 3 | | | | | | | |
| 5 | | | | | | | |
| 7 | | | | | | | |
| 8 | 0.8 | | CH | CLAY, with sand & gravel, grey mottled orange/red, high plasticity, sand 24% fine to coarse grained, gravel 26% fine to coarse, very stiff to hard, moist (inferred alluvial deposits). | VSt-H | M | |
| 17 | | | | | | | |
| 13 | | | | | | | |
| 8 | | | | | | | |
| 9 | 1.3 | | CI | gravelly CLAY, with sand, grey mottled orange/red, medium plasticity, gravel sub angular medium to coarse, sand fine to coarse grained, hard, dry (inferred Haunted Hills Formation residual soil). | H | D | 1879-S20 |
| 12 | | | | | | | |
| 16 | 1.5 | | | TP25 Terminated at 1.5m | | | |
| | 2 | | | | | | |
| | 2.5 | | | | | | |
| | 3 | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




GroundScience

(03) 5282 1566

10 Dowsett St.
South Geelong, Victoria 3220

admin@groundscience.com.au

| | | | |
|--------------------------|-----------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP25 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S20
Date Sampled: 19/05/2023
Dates Tested: 24/05/2023 - 13/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP25, Depth: 0.8m - 1.3m
Material: CH - CLAY, with sand & gravel, grey mottled orange/red, high plasticity, sand 24% fine to coarse grained, gravel 26% fine to coarse, very stiff to hard, moist (inferred alluvial deposits).


Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109


| Particle Size Distribution (AS1289 3.6.1) | | | | |
|---|----------|----------------|------------|-----------------|
| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
| 53 mm | 100 | | 0 | |
| 37.5 mm | 97 | | 3 | |
| 26.5 mm | 92 | | 4 | |
| 19 mm | 89 | | 3 | |
| 13.2 mm | 86 | | 3 | |
| 9.5 mm | 83 | | 3 | |
| 6.7 mm | 80 | | 3 | |
| 4.75 mm | 78 | | 2 | |
| 2.36 mm | 74 | | 3 | |
| 1.18 mm | 69 | | 5 | |
| 0.6 mm | 63 | | 6 | |
| 0.425 mm | 60 | | 3 | |
| 0.3 mm | 58 | | 2 | |
| 0.15 mm | 55 | | 2 | |
| 0.075 mm | 50 | | 5 | |



| Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1) | | Min | Max |
|--|------------|-----|-----|
| Sample History | Oven Dried | | |
| Preparation Method | Dry Sieve | | |
| Liquid Limit (%) | 70 | | |
| Plastic Limit (%) | 27 | | |
| Plasticity Index (%) | 43 | | |

| Linear Shrinkage (AS1289 3.4.1) | | Min | Max |
|----------------------------------|--------------------|-----|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | | |
| Linear Shrinkage (%) | 12.0 | | |
| Cracking Crumbling Curling | Cracking & Curling | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566

Engineering Log - Testpit

Testpit No: TP26

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.885686 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.619593 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 1.5m | Reviewed By : | Location : FORGE CREEK |
| | Date : 19/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-------------------------|-----------|-------------|---------------------|--|-------------|----------|---------|
| | | | | | | | |
| 1 | 0.2 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft, moist, organics. | S | M | |
| 2 | | | CL | As above, grey brown, gravel fine to coarse. | F | M | |
| 2 | 1.5 | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, firm to stiff, moist (inferred alluvial deposits). | F-St | M | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| TP26 Terminated at 1.5m | | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




 (03) 5282 1566
 10 Dowsett St.
 South Geelong, Victoria 3220
 admin@groundscience.com.au

| | | | |
|--------------------------|-----------------------|-----------------|----------------|
| Photo description | Test Pit Photos | | |
| Client | SMC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | TP26 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566

Engineering Log - Testpit

Testpit No: LP1P01

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.883339 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.618684 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 3m | Reviewed By : | Location : FORGE CREEK |
| | Date : 18/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-----------|-----------|-------------|---------------------|--|-------------|----------|--------------------|
| | | | | | | | Bulk Sample |
| 1 | 0.2 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft to firm, moist, organics. | S-F | M | |
| 2 | | | | | | | |
| 3 | | | CL | As above, stiff, dry to moist. | St | D-M | |
| 3 | 0.4 | | CI | sandy CLAY, orange mottled grey, medium plasticity, sand 44% fine to coarse grained, stiff to very stiff, dry to moist (inferred alluvial deposits). | St-VSt | D-M | |
| 4 | | | | | | | |
| 4 | | | | | | | |
| 5 | | | | | | | |
| 5 | | | | | | | |
| 6 | | | | | | | |
| 6 | | | | | | | |
| 7 | | | | | | | |
| 8 | | | | | | | |
| 9 | | | | | | | |
| 9 | | | | | | | |
| 9 | | | | | | | |
| | 1.5 | | CH | sandy CLAY, trace gravel, grey mottled red/orange, high plasticity, sand fine to coarse grained, gravel fine, hard, dry to moist (inferred Haunted Hills Formation residual soil). | H | D-M | 1879-S21, 1879-S25 |
| 2 | | | | | | | |
| | 2.5 | | | | | | |
| | | | | | | | |
| | 3 | | | | | | |
| | | | | | | | |
| | 3.5 | | | | | | |
| | | | | | | | |
| | | | | PTP01 Terminated at 3m | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




 (03) 5282 1566
 10 Dowsett St.
 South Geelong, Victoria 3220
 admin@groundscience.com.au

| | | | |
|--------------------------|-------------------------------|-----------------|----------------|
| Photo description | Leachate Pond Test Pit Photos | | |
| Client | SMC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | LPTP01 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S21
Date Sampled: 18/05/2023
Dates Tested: 24/05/2023 - 08/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: LPTP01, Depth: 0.4m - 2.0m
Material: CI - sandy CLAY, orange mottled grey, medium plasticity, sand 44% fine to coarse grained, stiff to very stiff, dry to moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

Particle Size Distribution (AS1289 3.6.1)

| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
|----------|----------|----------------|------------|-----------------|
| 6.7 mm | 100 | | 0 | |
| 4.75 mm | 100 | | 0 | |
| 2.36 mm | 100 | | 0 | |
| 1.18 mm | 99 | | 1 | |
| 0.6 mm | 95 | | 4 | |
| 0.425 mm | 90 | | 5 | |
| 0.3 mm | 84 | | 6 | |
| 0.15 mm | 73 | | 11 | |
| 0.075 mm | 56 | | 17 | |


Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1)

| | Min | Max |
|----------------------|------------|-----|
| Sample History | Oven Dried | |
| Preparation Method | Dry Sieve | |
| Liquid Limit (%) | 40 | |
| Plastic Limit (%) | 12 | |
| Plasticity Index (%) | 28 | |

Linear Shrinkage (AS1289 3.4.1)

| | Min | Max |
|----------------------------------|--------------------|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | |
| Linear Shrinkage (%) | 9.5 | |
| Cracking Crumbling Curling | Cracking & Curling | |

Particle Size Distribution



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S21
Date Sampled: 18/05/2023
Dates Tested: 24/05/2023 - 19/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: LPTP01, Depth: 0.4m - 2.0m
Material: Cl - sandy CLAY, orange mottled grey, medium plasticity, sand 44% fine to coarse grained, stiff to very stiff, dry to moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au



Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| California Bearing Ratio (AS 1289 6.1.1 & 2.1.1) | | Min | Max |
|--|-----------------------|-----|-----|
| CBR taken at | 2.5 mm | | |
| CBR % | 4.5 | | |
| Method of Compactive Effort | Standard | | |
| Method used to Determine MDD | AS 1289 5.1.1 & 2.1.1 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Maximum Dry Density (t/m ³) | 1.77 | | |
| Optimum Moisture Content (%) | 16.5 | | |
| Laboratory Density Ratio (%) | 99.0 | | |
| Laboratory Moisture Ratio (%) | 97.5 | | |
| Dry Density after Soaking (t/m ³) | 1.74 | | |
| Field Moisture Content (%) | | | |
| Moisture Content at Placement (%) | 16.2 | | |
| Moisture Content Top 30mm (%) | 19.1 | | |
| Moisture Content Rest of Sample (%) | 16.9 | | |
| Mass Surcharge (kg) | 4.5 | | |
| Soaking Period (days) | 4 | | |
| Curing Hours | 361.8 | | |
| Swell (%) | 1.0 | | |
| Oversize Material (mm) | 19 | | |
| Oversize Material Included | Excluded | | |
| Oversize Material (%) | 0.0 | | |
| Sample remoulded as per Vic Roads Code of Practice RC 500.16 | | | |

| Dry Density - Moisture Relationship (AS 1289 5.1.1 & 2.1.1) | | Min | Max |
|---|-------------------|-----|-----|
| Mould Type | 1 LITRE MOULD A | | |
| Compaction | Standard | | |
| Maximum Dry Density (t/m ³) | 1.77 | | |
| Optimum Moisture Content (%) | 16.5 | | |
| Oversize Sieve (mm) | 19.0 | | |
| Oversize Material Wet (%) | 0 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Curing Hours (h) | 143.5 | | |





Ground Science

A C N 105 704 078
 13 Brock Street Thomastown VIC, P 03 9464 4617 Email reception@groundscience.com.au

PERMEABILITY - CONSTANT HEAD (Triaxial method) AS1289 6.7.3

| | | | |
|--|---|--|--|
| Client : | Ground Science South West Pty Ltd | Job No. | GS6742/1 |
| Project: | GSSW1879 | Report No. | DM |
| Location: | Forge Creek | Test date: | 20-Jun-23 |
| Sample number | #S159 | | |
| Borehole / test pit | LPTP01 | | |
| Depth, m | 0.4m - 2.0m | | |
| Sample diameter | mm | 63.26 | |
| Sample height | mm | 63.18 | |
| Specimen wet density | t/m ³ | 2.022 | |
| Specimen dry density | t/m ³ | 1.73 | |
| Moisture content | % | 16.8 | |
| Cell pressure | kPa | 560 | |
| Inlet pressure | kPa | 520 | |
| Outlet pressure | kPa | 500 | |
| Mean effective stress | kPa | 50 | |
| Hydraulic head | kPa | 20 | |
| Saturation | % | 98 | |
| PERMEABILITY | m/sec | 1.E-10 | |
| Water type | de-aired - filtered | | |
| Specimen description | CLAY, medium to high plasticity, brown | | |
| Notes: | Sample remoulded to a target of 98% SMDD @ OMC MDD = 1.77 t/m ³ OMC = 16.6 % Density Ratio = 98 % | | |
| Comments | Sampled by client, tested as received MDD and OMC Supplied by client | | |
|  <p>ACCREDITED FOR TECHNICAL COMPETENCE</p> | | NATA Accredited Laboratory No. 15055 Accredited for compliance with ISO/IEC 17025 - Testing | Date of issue 27/06/2023 Aaron Stuart Approved Signatory |



Ground Science

A C N 105 704 078
 13 Brock Street Thomastown VIC, P 03 9464 4617 Email reception@groundscience.com.au

PERMEABILITY - CONSTANT HEAD (Triaxial method) AS1289 6.7.3

| | | | |
|--|---|--|--|
| Client : | Ground Science South West Pty Ltd | Job No. | GS6742/1 |
| Project: | GSSW1879 | Report No. | DW |
| Location: | Forge Creek | Test date: | 20-Jun-23 |
| Sample number | #S159 | | |
| Borehole / test pit | LPTP01 | | |
| Depth, m | 0.4m - 2.0m | | |
| Sample diameter | mm | 63.26 | |
| Sample height | mm | 63.18 | |
| Specimen wet density | t/m3 | 2.022 | |
| Specimen dry density | t/m3 | 1.73 | |
| Moisture content | % | 16.8 | |
| Cell pressure | kPa | 560 | |
| Inlet pressure | kPa | 520 | |
| Outlet pressure | kPa | 500 | |
| Mean effective stress | kPa | 50 | |
| Hydraulic head | kPa | 20 | |
| Saturation | % | 98 | |
| PERMEABILITY | m/sec | 9.E-11 | |
| Water type | 50,000ppm NaCl Solution | | |
| Specimen description | CLAY, medium to high plasticity, brown | | |
| Notes: | Sample remoulded to a target of 98% SMDD @ OMC MDD = 1.77 t/m3 OMC = 16.6 % Density Ratio = 98 % | | |
| Comments | Sampled by client, tested as received MDD and OMC Supplied by client | | |
|  <p>ACCREDITED FOR TECHNICAL COMPETENCE</p> | | NATA Accredited Laboratory No. 15055 Accredited for compliance with ISO/IEC 17025 - Testing | Date of issue 27/06/2023 Aaron Stuart Approved Signatory |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566

Engineering Log Testpit

Testpit No: LP1P02

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.883403 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.618488 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 3m | Reviewed By : | Location : FORGE CREEK |
| | Date : 18/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-----------|-----------|-------------|---------------------|--|-------------|----------|-------------|
| | | | | | | | Bulk Sample |
| 1 | 0.2 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft to firm, moist, organics. | S-F | M | |
| 2 | | | | | | | |
| 2 | 0.5 | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, firm to stiff, moist (inferred alluvial deposits). | F-St | M | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 3 | 0.75 | | CI | CLAY, trace sand, orange mottled grey, medium plasticity, sand fine to medium grained, stiff, dry to moist (inferred alluvial deposits). | St | D-M | |
| 3 | | | | | | | |
| 4 | | | | | | | |
| 3 | 1 | | | | | | |
| 3 | | | | | | | |
| 3 | | | | | | | |
| 4 | 1.2 | | CH | sandy CLAY, grey mottled red/orange, high plasticity, sand 56% fine to coarse grained, stiff, dry to moist (inferred Haunted Hills Formation residual soil). | St | D-M | |
| 4 | | | | | | | |
| 5 | | | | | | | |
| | 1.5 | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | 2 | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | 2.5 | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | 3 | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | 3.5 | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | PTP02 Terminated at 3m | | | 1879-S22 |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




 (03) 5282 1566
 10 Dowsett St.
 South Geelong, Victoria 3220
 admin@groundscience.com.au

| | | | |
|--------------------------|-------------------------------|-----------------|----------------|
| Photo description | Leachate Pond Test Pit Photos | | |
| Client | SMEC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | LPTP01 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S22
Date Sampled: 18/05/2023
Dates Tested: 24/05/2023 - 07/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: LPTP02, Depth: 1.2m - 3.0m
Material: CH - sandy CLAY (organics), grey mottled red/orange, high plasticity, sand 56% fine to coarse grained, stiff, dry to moist (inferred Haunted Hills Formation residual soil).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

Particle Size Distribution (AS1289 3.6.1)

| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
|----------|----------|----------------|------------|-----------------|
| 4.75 mm | 100 | | 0 | |
| 2.36 mm | 100 | | 0 | |
| 1.18 mm | 97 | | 3 | |
| 0.6 mm | 80 | | 17 | |
| 0.425 mm | 61 | | 19 | |
| 0.3 mm | 52 | | 9 | |
| 0.15 mm | 48 | | 4 | |
| 0.075 mm | 44 | | 4 | |


Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1)

| | Min | Max |
|----------------------|------------|-----|
| Sample History | Oven Dried | |
| Preparation Method | Dry Sieve | |
| Liquid Limit (%) | 61 | |
| Plastic Limit (%) | 20 | |
| Plasticity Index (%) | 41 | |

Linear Shrinkage (AS1289 3.4.1)

| | Min | Max |
|----------------------------------|---------------|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | |
| Linear Shrinkage (%) | 12.0 | |
| Cracking Crumbling Curling | Curling | |

Particle Size Distribution



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S22
Date Sampled: 18/05/2023
Dates Tested: 24/05/2023 - 19/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: LPTP02, Depth: 1.2m - 3.0m
Material: CH - sandy CLAY (organics), grey mottled red/orange, high plasticity, sand 56% fine to coarse grained, stiff, dry to moist (inferred Haunted Hills Formation residual soil).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au



Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| California Bearing Ratio (AS 1289 6.1.1 & 2.1.1) | | Min | Max |
|--|-----------------------|-----|-----|
| CBR taken at | 2.5 mm | | |
| CBR % | 2.5 | | |
| Method of Compactive Effort | Standard | | |
| Method used to Determine MDD | AS 1289 5.1.1 & 2.1.1 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Maximum Dry Density (t/m ³) | 1.81 | | |
| Optimum Moisture Content (%) | 15.0 | | |
| Laboratory Density Ratio (%) | 98.0 | | |
| Laboratory Moisture Ratio (%) | 99.5 | | |
| Dry Density after Soaking (t/m ³) | 1.73 | | |
| Field Moisture Content (%) | | | |
| Moisture Content at Placement (%) | 14.8 | | |
| Moisture Content Top 30mm (%) | 21.3 | | |
| Moisture Content Rest of Sample (%) | 16.1 | | |
| Mass Surcharge (kg) | 4.5 | | |
| Soaking Period (days) | 4 | | |
| Curing Hours | 361.8 | | |
| Swell (%) | 2.5 | | |
| Oversize Material (mm) | 19 | | |
| Oversize Material Included | Excluded | | |
| Oversize Material (%) | 0.0 | | |
| Sample remoulded as per Vic Roads Code of Practice RC 500.16 | | | |

| Dry Density - Moisture Relationship (AS 1289 5.1.1 & 2.1.1) | | Min | Max |
|---|-------------------|-----|-----|
| Mould Type | 1 LITRE MOULD A | | |
| Compaction | Standard | | |
| Maximum Dry Density (t/m ³) | 1.81 | | |
| Optimum Moisture Content (%) | 15.0 | | |
| Oversize Sieve (mm) | 19.0 | | |
| Oversize Material Wet (%) | 0 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Curing Hours (h) | 151.4 | | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566


Engineering Log - Testpit

Testpit No: LP TP03

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.883536 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.618638 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 3m | Reviewed By : | Location : FORGE CREEK |
| | Date : 18/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples |
|-----------|-----------|-------------|---------------------|--|-------------|----------|-------------|
| | | | | | | | Bulk Sample |
| 1 | 0.2 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft to firm, moist, organics. | S-F | M | |
| 2 | | | | | | | |
| 3 | 0.5 | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, firm to stiff, moist (inferred alluvial deposits). | F-St | M | |
| 3 | | | | | | | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 2 | 0.7 | | CI | CLAY, trace sand, orange mottled grey, medium plasticity, sand fine to medium grained, firm, moist (inferred alluvial deposits). | F | M | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 2 | 1.2 | | CH | sandy CLAY, trace gravel, grey mottled red/orange, high plasticity, sand 54% fine to coarse grained, gravel 1%, firm to stiff, moist (inferred Haunted Hills Formation residual soil). | F-St | M | |
| 2 | | | | | | | |
| 2 | | | | | | | |
| 3 | | | | | | | |
| | 1.5 | | | | | | |
| | | | | | | | |
| | 2 | | | | | | |
| | | | | | | | |
| | 2.5 | | CH | As above, grey mottled orange, stiff. | St | M | 1879-S23 |
| | | | | | | | |
| | 3 | | | | | | |
| | | | | | | | |
| | 3.5 | | | | | | |
| | | | | | | | |
| | | | | PTP03 Terminated at 3m | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




 (03) 5282 1566
 10 Dowsett St.
 South Geelong, Victoria 3220
 admin@groundscience.com.au

| | | | |
|--------------------------|-------------------------------|-----------------|----------------|
| Photo description | Leachate Pond Test Pit Photos | | |
| Client | SMC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | LPTP01 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S23
Date Sampled: 18/05/2023
Dates Tested: 24/05/2023 - 08/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: LPTP03, Depth: 1.2m - 2.5m
Material: CH - sandy CLAY, trace gravel, grey mottled red/orange, high plasticity, sand 54% fine to coarse grained, gravel 1%, firm to stiff, moist (inferred Haunted Hills Formation residual soil).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

Particle Size Distribution (AS1289 3.6.1)

| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
|----------|----------|----------------|------------|-----------------|
| 9.5 mm | 100 | | 0 | |
| 6.7 mm | 100 | | 0 | |
| 4.75 mm | 100 | | 0 | |
| 2.36 mm | 99 | | 0 | |
| 1.18 mm | 96 | | 4 | |
| 0.6 mm | 71 | | 25 | |
| 0.425 mm | 60 | | 11 | |
| 0.3 mm | 55 | | 5 | |
| 0.15 mm | 50 | | 4 | |
| 0.075 mm | 45 | | 5 | |

Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1)

| | Min | Max |
|----------------------|------------|-----|
| Sample History | Oven Dried | |
| Preparation Method | Dry Sieve | |
| Liquid Limit (%) | 52 | |
| Plastic Limit (%) | 16 | |
| Plasticity Index (%) | 36 | |

Linear Shrinkage (AS1289 3.4.1)

| | Min | Max |
|----------------------------------|---------------|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | |
| Linear Shrinkage (%) | 9.0 | |
| Cracking Crumbling Curling | Curling | |

Particle Size Distribution



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S23
Date Sampled: 18/05/2023
Dates Tested: 24/05/2023 - 19/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: LPTP03, Depth: 1.2m - 2.5m
Material: CH - sandy CLAY, trace gravel, grey mottled red/orange, high plasticity, sand 54% fine to coarse grained, gravel 1%, firm to stiff, moist (inferred Haunted Hills Formation residual soil).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au



Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| California Bearing Ratio (AS 1289 6.1.1 & 2.1.1) | | Min | Max |
|--|-----------------------|-----|-----|
| CBR taken at | 2.5 mm | | |
| CBR % | 3.0 | | |
| Method of Compactive Effort | Standard | | |
| Method used to Determine MDD | AS 1289 5.1.1 & 2.1.1 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Maximum Dry Density (t/m ³) | 1.83 | | |
| Optimum Moisture Content (%) | 15.0 | | |
| Laboratory Density Ratio (%) | 98.0 | | |
| Laboratory Moisture Ratio (%) | 101.0 | | |
| Dry Density after Soaking (t/m ³) | 1.77 | | |
| Field Moisture Content (%) | | | |
| Moisture Content at Placement (%) | 15.0 | | |
| Moisture Content Top 30mm (%) | 17.7 | | |
| Moisture Content Rest of Sample (%) | 15.9 | | |
| Mass Surcharge (kg) | 4.5 | | |
| Soaking Period (days) | 4 | | |
| Curing Hours | 361.6 | | |
| Swell (%) | 1.5 | | |
| Oversize Material (mm) | 19 | | |
| Oversize Material Included | Excluded | | |
| Oversize Material (%) | 0.0 | | |
| Sample remoulded as per Vic Roads Code of Practice RC 500.16 | | | |

| Dry Density - Moisture Relationship (AS 1289 5.1.1 & 2.1.1) | | Min | Max |
|---|-------------------|-----|-----|
| Mould Type | 1 LITRE MOULD A | | |
| Compaction | Standard | | |
| Maximum Dry Density (t/m ³) | 1.83 | | |
| Optimum Moisture Content (%) | 15.0 | | |
| Oversize Sieve (mm) | 19.0 | | |
| Oversize Material Wet (%) | 0 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Curing Hours (h) | 143.5 | | |



This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Ground Science South West
 10 Dowsett St, South Geelong, Victoria 3220
 Phone: (03) 5282 1566

Engineering Log - Testpit
Testpit No: LP TP04

| | | |
|--------------------------|--|---------------------------------|
| Latitude : -37.883617 | Excavator : Yanmar VIO17 | Job Number : GSSW1879 |
| Longitude : 147.618441 | Excavator Supplier : Ground Science South West | Client : SMEC AUSTRALIA PTY LTD |
| Elevation : Not Surveyed | Logged By : MK | Project : EGSC COMPOST FACILITY |
| Total Depth : 3m | Reviewed By : | Location : FORGE CREEK |
| | Date : 18/05/2023 | Loc Comment : |

| DCP graph | Depth (m) | Graphic Log | Classification Code | Material Description | Consistency | Moisture | Samples | |
|-----------|-----------|-------------|-------------------------------|---|-------------|----------|-----------------------|--|
| | | | | | | | Bulk Sample | |
| 1 | 0.25 | | CL | TOPSOIL: gravelly, sandy, silty CLAY, brown, low plasticity, sand fine to coarse grained, gravel sub angular to sub rounded fine, soft, moist, organics. | S | M | | |
| 1 | | | CH | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, soft to firm, moist (inferred alluvial deposits). | S-F | M | | |
| 1 | 0.55 | | CL | sandy CLAY, orange mottled grey, low plasticity, sand 35% fine to coarse grained, stiff to very stiff, moist (inferred alluvial deposits). | St-VSt | M | | |
| 1 | | | | | | | | |
| 4 | | | | | | | | |
| 5 | | | | | | | | |
| 6 | | | | | | | | |
| 6 | | | | | | | | |
| 6 | | | | | | | | |
| 6 | | | | | | | | |
| 7 | | | | | | | | |
| 8 | | | | | | | | |
| 1 | 1.5 | | | | | | | |
| 6 | | | | | | | | |
| 6 | | | | | | | | |
| 6 | | | | | | | | |
| 6 | | | | | | | | |
| 6 | | | | | | | | |
| 6 | | | | | | | | |
| 6 | | | | | | | | |
| 6 | | | | | | | | |
| 6 | | | | | | | | |
| 1 | 2.5 | | CH | sandy CLAY, trace gravel, grey mottled red/orange, high plasticity, sand fine to coarse grained, gravel fine, very stiff to hard, dry (inferred Haunted Hills Formation residual soil). | VSt-H | D | 1879-S24, 1879-S26 | |
| 1 | | | | | | | | |
| 1 | 3 | | PTP04 Terminated at 3m | | | | | |
| 1 | | | | | | | | |
| 1 | | | | | | | | |
| 1 | | | | | | | | |
| 1 | 3.5 | | | | | | | |
| 1 | | | | | | | | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.




 (03) 5282 1566
 10 Dowsett St.
 South Geelong, Victoria 3220
 admin@groundscience.com.au

| | | | |
|--------------------------|-------------------------------|-----------------|----------------|
| Photo description | Leachate Pond Test Pit Photos | | |
| Client | SMC AUSTRALIA PTY LTD | | |
| Location | FORGE CREEK | | |
| Project name | EGSC COMPOST FACILITY | | |
| Project No | GSSW1879 | Scale | Not to Scale |
| TP No | LPTP01 | TP Depth | Not Applicable |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S24
Date Sampled: 18/05/2023
Dates Tested: 24/05/2023 - 08/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: LPTP04, Depth: 0.55m - 2.5m
Material: CH - sandy CLAY, orange mottled grey, high plasticity, sand 35% fine to coarse grained, stiff to very stiff, moist (inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing




Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| Particle Size Distribution (AS1289 3.6.1) | | | | |
|---|----------|----------------|------------|-----------------|
| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
| 19 mm | 100 | | 0 | |
| 13.2 mm | 100 | | 0 | |
| 9.5 mm | 100 | | 0 | |
| 6.7 mm | 100 | | 0 | |
| 4.75 mm | 100 | | 0 | |
| 2.36 mm | 100 | | 0 | |
| 1.18 mm | 100 | | 0 | |
| 0.6 mm | 97 | | 3 | |
| 0.425 mm | 93 | | 4 | |
| 0.3 mm | 87 | | 5 | |
| 0.15 mm | 79 | | 9 | |
| 0.075 mm | 65 | | 14 | |

| Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1) | | Min | Max |
|--|------------|-----|-----|
| Sample History | Oven Dried | | |
| Preparation Method | Dry Sieve | | |
| Liquid Limit (%) | 61 | | |
| Plastic Limit (%) | 18 | | |
| Plasticity Index (%) | 43 | | |

| Linear Shrinkage (AS1289 3.4.1) | | Min | Max |
|----------------------------------|--------------------|-----|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | | |
| Linear Shrinkage (%) | 12.0 | | |
| Cracking Crumbling Curling | Cracking & Curling | | |



Material Test Report

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S24
Date Sampled: 18/05/2023
Dates Tested: 24/05/2023 - 19/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: LTP04, Depth: 0.55m - 2.5m
Material: CH - sandy CLAY, orange mottled grey, high plasticity, sand 35% fine to coarse grained, stiff to very stiff, moist (inferred alluvial deposits).



Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au



Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| California Bearing Ratio (AS 1289 6.1.1 & 2.1.1) | | Min | Max |
|--|-----------------------|-----|-----|
| CBR taken at | 2.5 mm | | |
| CBR % | 1.5 | | |
| Method of Compactive Effort | Standard | | |
| Method used to Determine MDD | AS 1289 5.1.1 & 2.1.1 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Maximum Dry Density (t/m ³) | 1.88 | | |
| Optimum Moisture Content (%) | 15.0 | | |
| Laboratory Density Ratio (%) | 97.5 | | |
| Laboratory Moisture Ratio (%) | 97.0 | | |
| Dry Density after Soaking (t/m ³) | 1.80 | | |
| Field Moisture Content (%) | | | |
| Moisture Content at Placement (%) | 14.4 | | |
| Moisture Content Top 30mm (%) | 21.1 | | |
| Moisture Content Rest of Sample (%) | 15.4 | | |
| Mass Surcharge (kg) | 4.5 | | |
| Soaking Period (days) | 4 | | |
| Curing Hours | 361.3 | | |
| Swell (%) | 2.0 | | |
| Oversize Material (mm) | 19 | | |
| Oversize Material Included | Excluded | | |
| Oversize Material (%) | 0.0 | | |
| Sample remoulded as per Vic Roads Code of Practice RC 500.16 | | | |

| Dry Density - Moisture Relationship (AS 1289 5.1.1 & 2.1.1) | | Min | Max |
|---|-------------------|-----|-----|
| Mould Type | 1 LITRE MOULD A | | |
| Compaction | Standard | | |
| Maximum Dry Density (t/m ³) | 1.88 | | |
| Optimum Moisture Content (%) | 15.0 | | |
| Oversize Sieve (mm) | 19.0 | | |
| Oversize Material Wet (%) | 0 | | |
| Method used to Determine Plasticity | Visual Assessment | | |
| Curing Hours (h) | 150.8 | | |





Ground Science

A C N 105 704 078
 13 Brock Street Thomastown VIC, P 03 9464 4617 Email reception@groundscience.com.au

PERMEABILITY - CONSTANT HEAD (Triaxial method) AS1289 6.7.3

| | | | |
|--|---|--|--|
| Client : | Ground Science South West Pty Ltd | Job No. | GS6742/1 |
| Project: | GSSW1879 | Report No. | DN |
| Location: | Forge Creek | Test date: | 16-Jun-23 |
| Sample number | #S160 | | |
| Borehole / test pit | LPTP04 | | |
| Depth, m | 0.55m - 2.5m | | |
| Sample diameter | mm | 63.26 | |
| Sample height | mm | 63.18 | |
| Specimen wet density | t/m3 | 2.123 | |
| Specimen dry density | t/m3 | 1.84 | |
| Moisture content | % | 15.4 | |
| Cell pressure | kPa | 560 | |
| Inlet pressure | kPa | 520 | |
| Outlet pressure | kPa | 500 | |
| Mean effective stress | kPa | 50 | |
| Hydraulic head | kPa | 20 | |
| Saturation | % | 98 | |
| PERMEABILITY | m/sec | 4.E-11 | |
| Water type | de-aired - filtered | | |
| Specimen description | sandy CLAY, medium plasticity, brown | | |
| Notes: | Sample remoulded to a target of 98% SMDD @ OMC MDD = 1.88 t/m3 OMC = 14.9 % Density Ratio = 98 % | | |
| Comments | Sampled by client, tested as received MDD and OMC Supplied by client | | |
|  <p>ACCREDITED FOR TECHNICAL COMPETENCE</p> | | NATA Accredited Laboratory No. 15055 Accredited for compliance with ISO/IEC 17025 - Testing | Date of issue 27/06/2023 Aaron Stuart Approved Signatory |



Ground Science

A C N 105 704 078
 13 Brock Street Thomastown VIC, P 03 9464 4617 Email reception@groundscience.com.au

PERMEABILITY - CONSTANT HEAD (Triaxial method) AS1289 6.7.3

| | | | |
|---|---|--|------------------|
| Client : | Ground Science South West Pty Ltd | Job No. | GS6742/1 |
| Project: | GSSW1879 | Report No. | DX |
| Location: | Forge Creek | Test date: | 16-Jun-23 |
| Sample number | #S160 | | |
| Borehole / test pit | LPTP04 | | |
| Depth, m | 0.55m - 2.5m | | |
| Sample diameter | mm | 63.26 | |
| Sample height | mm | 63.18 | |
| Specimen wet density | t/m ³ | 2.123 | |
| Specimen dry density | t/m ³ | 1.84 | |
| Moisture content | % | 15.4 | |
| Cell pressure | kPa | 560 | |
| Inlet pressure | kPa | 520 | |
| Outlet pressure | kPa | 500 | |
| Mean effective stress | kPa | 50 | |
| Hydraulic head | kPa | 20 | |
| Saturation | % | 98 | |
| PERMEABILITY | m/sec | 2.E-11 | |
| Water type | 50,000ppm NaCl Solution | | |
| Specimen description | sandy CLAY, medium plasticity, brown | | |
| Notes: | Sample remoulded to a target of 98% SMDD @ OMC MDD = 1.88 t/m ³ OMC = 14.9 % Density Ratio = 98 % | | |
| Comments | Sampled by client, tested as received MDD and OMC Supplied by client | | |
|  ACCREDITED FOR TECHNICAL COMPETENCE | | NATA Accredited Laboratory No. 15055 Accredited for compliance with ISO/IEC 17025 - Testing | |
| | | Date of issue | 27/06/2023 |
| | | Aaron Stuart | |
| | | Approved Signatory | |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.



Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Sample Number: 1879-S27
Date Sampled: 19/05/2023
Dates Tested: 24/05/2023 - 13/06/2023
Sampling Method: AS 1289.1.2.1 6.5.4 - Machine excavated pit or trench
Remarks: Material classified as per AS 1726:2017
Sample Location: TP19 + TP24 + TP25 + TP26, Depth: 0.4m - 1.5m
Material: CH - CLAY, with sand & trace gravel, orange mottled brown, high plasticity, sand 16% fine to coarse grained, gravel 10% fine to medium, stiff, moist (Inferred alluvial deposits).

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing




Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

| Particle Size Distribution (AS1289 3.6.1) | | | | |
|---|----------|----------------|------------|-----------------|
| Sieve | Passed % | Passing Limits | Retained % | Retained Limits |
| 26.5 mm | 100 | | 0 | |
| 19 mm | 99 | | 1 | |
| 13.2 mm | 98 | | 1 | |
| 9.5 mm | 96 | | 3 | |
| 6.7 mm | 93 | | 2 | |
| 4.75 mm | 92 | | 1 | |
| 2.36 mm | 90 | | 2 | |
| 1.18 mm | 88 | | 2 | |
| 0.6 mm | 84 | | 4 | |
| 0.425 mm | 81 | | 2 | |
| 0.3 mm | 80 | | 2 | |
| 0.15 mm | 77 | | 2 | |
| 0.075 mm | 74 | | 4 | |

| Atterberg Limit (AS1289 3.1.2 & 3.2.1 & 3.3.1) | | Min | Max |
|--|------------|-----|-----|
| Sample History | Oven Dried | | |
| Preparation Method | Dry Sieve | | |
| Liquid Limit (%) | 69 | | |
| Plastic Limit (%) | 28 | | |
| Plasticity Index (%) | 41 | | |

| Linear Shrinkage (AS1289 3.4.1) | | Min | Max |
|----------------------------------|--------------------|-----|-----|
| Moisture Condition Determined By | AS 1289.3.1.2 | | |
| Linear Shrinkage (%) | 12.5 | | |
| Cracking Crumbling Curling | Cracking & Curling | | |





Ground Science

A C N 105 704 078
 13 Brock Street Thomastown VIC, P 03 9464 4617 Email reception@groundscience.com.au

PERMEABILITY - CONSTANT HEAD (Triaxial method) AS1289 6.7.3

| | | | |
|---|---|--|--|
| Client : | Ground Science South West Pty Ltd | Job No. | GS6742/1 |
| Project: | GSSW1879 | Report No. | DO |
| Location: | Forge Creek | Test date: | 19-Jun-23 |
| Sample number | #S161 | | |
| Borehole / test pit | TP19 + TP24 + TP25 + TP26 | | |
| Depth, m | 0.4-1.5M | | |
| Sample diameter | mm | 63.26 | |
| Sample height | mm | 63.10 | |
| Specimen wet density | t/m3 | 1.839 | |
| Specimen dry density | t/m3 | 1.43 | |
| Moisture content | % | 28.2 | |
| Cell pressure | kPa | 560 | |
| Inlet pressure | kPa | 520 | |
| Outlet pressure | kPa | 500 | |
| Mean effective stress | kPa | 50 | |
| Hydraulic head | kPa | 20 | |
| Saturation | % | 98 | |
| PERMEABILITY | m/sec | 3.E-10 | |
| Water type | de-aired - filtered | | |
| Specimen description | CLAY, medium to high plasticity, brown, with gravel | | |
| Notes: | Sample remoulded to a target of 98% SMDD @ OMC MDD = 1.46 t/m3 OMC = 28.4 % Density Ratio = 98 % | | |
| Comments | Sampled by client, tested as received MDD and OMC Supplied by client | | |
|  ACCREDITED FOR TECHNICAL COMPETENCE | | NATA Accredited Laboratory No. 15055 Accredited for compliance with ISO/IEC 17025 - Testing | Date of issue 27/06/2023 Aaron Stuart Approved Signatory |



Ground Science

A C N 105 704 078
 13 Brock Street Thomastown VIC, P 03 9464 4617 Email reception@groundscience.com.au

PERMEABILITY - CONSTANT HEAD (Triaxial method) AS1289 6.7.3

| | | | |
|--|---|--|--|
| Client : | Ground Science South West Pty Ltd | Job No. | GS6742/1 |
| Project: | GSSW1879 | Report No. | DY |
| Location: | Forge Creek | Test date: | 19-Jun-23 |
| Sample number | #S161 | | |
| Borehole / test pit | TP19 + TP24 + TP25 + TP26 | | |
| Depth, m | 0.4-1.5M | | |
| Sample diameter | mm | 63.26 | |
| Sample height | mm | 63.10 | |
| Specimen wet density | t/m3 | 1.839 | |
| Specimen dry density | t/m3 | 1.43 | |
| Moisture content | % | 28.2 | |
| Cell pressure | kPa | 560 | |
| Inlet pressure | kPa | 520 | |
| Outlet pressure | kPa | 500 | |
| Mean effective stress | kPa | 50 | |
| Hydraulic head | kPa | 20 | |
| Saturation | % | 98 | |
| PERMEABILITY | m/sec | 2.E-10 | |
| Water type | 50,000ppm NaCl Solution | | |
| Specimen description | CLAY, medium to high plasticity, brown, with gravel | | |
| Notes: | Sample remoulded to a target of 98% SMDD @ OMC MDD = 1.46 t/m3 OMC = 28.4 % Density Ratio = 98 % | | |
| Comments | Sampled by client, tested as received MDD and OMC Supplied by client | | |
|  <p>ACCREDITED FOR TECHNICAL COMPETENCE</p> | | NATA Accredited Laboratory No. 15055 Accredited for compliance with ISO/IEC 17025 - Testing | Date of issue 27/06/2023 Aaron Stuart Approved Signatory |

Material Test Report

Report Number: GSSW1879-1
Issue Number: 1
Date Issued: 21/06/2023
Client: SMEC AUSTRALIA PTY LTD
 4/727 Collins St, Docklands Victoria 3008
Project Number: GSSW1879
Project Name: GEOTECHNICAL INVESTIGATION EGSC COMPOST FACILITY
Project Location: FORGE CREEK
Work Request: 15787
Dates Tested: 24/05/2023 - 25/05/2023

Ground Science South West
 Geotechnical & Environmental Consultants

Ground Science South West Pty Ltd
 10 Dowsett Street South Geelong Vic 3220
 Phone: (03) 5282 1566
 Email: chrism@groundscience.com.au

Accredited for compliance with ISO/IEC 17025 - Testing



Approved Signatory: Chris Mamalis
 Laboratory Manager
 NATA Accredited Laboratory Number: 20109

Moisture Content AS 1289 2.1.1

| Sample Number | Sample Location | Moisture Content (%) | Min | Max | Material |
|---------------|---------------------|----------------------|-----|-----|--|
| 1879-S29 | PD01 , Depth: 0.22m | 3.5 % | ** | ** | FILL: GC - sandy, clayey GRAVEL (River Gravel), orange mottled white, sub angular to rounded fine to coarse, low plasticity, sand 36% fine to coarse grained, dense, dry. |
| 1879-S30 | PD01 , Depth: 0.95m | 18.5 % | ** | ** | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine grained, gravel fine, very stiff to hard, dry to moist (inferred alluvial deposits). |
| 1879-S31 | SD01 , Depth: 0.2m | 5.2 % | ** | ** | FILL: GM-GC - sandy, silty/clayey GRAVEL (River Gravel), orange mottled white, sub angular to rounded fine to coarse, low plasticity, sand 34% fine to coarse grained, dense, dry. |
| 1879-S32 | SD01 , Depth: 0.78m | 5.7 % | ** | ** | FILL: GM-GC - sandy, silty/clayey GRAVEL (River Gravel), orange mottled white, sub angular to rounded fine to coarse, low plasticity, sand 34% fine to coarse grained, dense, dry. |
| 1879-S33 | PD02 , Depth: 0.21m | 3.6 % | ** | ** | FILL: GM-GC - sandy, silty/clayey GRAVEL (River Gravel), orange mottled white, sub angular to rounded fine to coarse, low plasticity, sand 32% fine to coarse grained, dense, dry. |
| 1879-S34 | PD02 , Depth: 0.91m | 13.9 % | ** | ** | CLAY, trace sand, orange mottled brown, low plasticity, sand fine grained, gravel fine, stiff to very stiff, moist (inferred alluvial deposits). |
| 1879-S35 | SD02 , Depth: 0.15m | 7.3 % | ** | ** | sandy, silty/clayey GRAVEL (River Gravel), orange mottled white, sub angular to rounded fine to coarse, low plasticity, sand fine to coarse grained, dense, dry. |
| 1879-S36 | SD02 , Depth: 0.9m | 17.2 % | ** | ** | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine grained, gravel fine, stiff to very stiff, dry to moist (inferred alluvial deposits). |
| 1879-S37 | TP01 , Depth: 1.4m | 18.4 % | ** | ** | CLAY, trace sand, orange mottled grey, medium plasticity, sand fine to medium grained, very stiff to hard, moist (inferred alluvial deposits). |
| 1879-S38 | TP02 , Depth: 1.75m | 15.7 % | ** | ** | CL - CLAY, trace sand, orange mottled grey, low plasticity, sand 10% fine to medium grained, very stiff to hard, moist (inferred alluvial deposits). |
| 1879-S39 | TP03 , Depth: 1.45m | 16.8 % | ** | ** | CL - CLAY, with sand, trace gravel, orange mottled brown, low plasticity, sand 19% fine to medium grained, gravel 1%, firm to stiff, dry to moist (inferred alluvial deposits). |
| 1879-S40 | TP04 , Depth: 1.7m | 16.8 % | ** | ** | CI - CLAY, with sand, orange mottled grey, medium plasticity, sand 19% fine to medium grained, stiff to very stiff, moist (inferred alluvial deposits). |
| 1879-S41 | TP05 , Depth: 1.47m | 19.1 % | ** | ** | sandy CLAY, orange mottled grey, medium plasticity, sand fine to coarse grained, very stiff to hard, moist (inferred alluvial deposits). |
| 1879-S42 | TP06 , Depth: 1.4m | 17.0 % | ** | ** | CLAY, trace sand, orange mottled grey, medium plasticity, sand fine to medium grained, very stiff to hard, moist (inferred alluvial deposits). |
| 1879-S43 | TP07 , Depth: 1.38m | 18.1 % | ** | ** | CLAY, trace sand, orange mottled grey, medium plasticity, sand fine to medium grained, very stiff to hard, dry to moist (inferred alluvial deposits). |
| 1879-S44 | TP08 , Depth: 1.3m | 16.5 % | ** | ** | CLAY, trace sand, orange mottled grey, medium plasticity, sand fine to medium grained, hard, dry to moist (inferred alluvial deposits). |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose other than such any copyright.

| Sample Number | Sample Location | Moisture Content (%) | Min | Max | Material |
|---------------|---------------------|----------------------|-----|-----|---|
| 1879-S45 | TP09 , Depth: 1.45m | 14.8 % | ** | | CLAY, trace sand, orange mottled grey, medium plasticity, sand fine to medium grained, stiff, dry to moist (inferred alluvial deposits). |
| 1879-S46 | TP10 , Depth: 1.5m | 15.7 % | ** | ** | CI - CLAY, with sand, orange mottled grey, medium plasticity, sand 25% fine to medium grained, very stiff to hard, dry to moist (inferred alluvial deposits). |
| 1879-S47 | TP11 , Depth: 1.48m | 20.1 % | ** | ** | CLAY, trace sand, orange mottled brown, high plasticity, sand fine to medium grained, stiff, moist (inferred alluvial deposits). |
| 1879-S48 | TP12 , Depth: 1.55m | 20.1 % | ** | ** | CH - CLAY, trace sand & gravel, orange mottled red/grey, high plasticity, sand 15% fine to medium grained, gravel 8% fine to medium, stiff to very stiff, moist (inferred alluvial deposits). |
| 1879-S49 | TP13 , Depth: 1.2m | 18.3 % | ** | ** | CI - CLAY, with sand, orange mottled brown, medium plasticity, sand 23% fine to medium grained, very stiff to hard, moist (inferred alluvial deposits). |
| 1879-S50 | TP14 , Depth: 1.5m | 16.3 % | ** | ** | CL - sandy CLAY, trace gravel, orange mottled grey, low plasticity, sand 40% fine to coarse grained, gravel 2%, stiff, moist (inferred alluvial deposits). |
| 1879-S51 | TP15 , Depth: 1.2m | 13.2 % | ** | ** | CI - sandy CLAY, trace gravel, orange mottled red/grey, medium plasticity, sand 45% fine to coarse grained, gravel 1%, very stiff to hard, dry (inferred Haunted Hills Formation residual soil). |
| 1879-S52 | TP16 , Depth: 1.2m | 14.9 % | ** | ** | CLAY, trace sand, orange mottled grey, medium plasticity, sand fine to medium grained, stiff to very stiff, dry to moist (inferred alluvial deposits). |
| 1879-S53 | TP17 , Depth: 1.3m | 14.9 % | ** | ** | CLAY, trace sand, orange mottled grey, medium plasticity, sand fine to medium grained, stiff to very stiff, dry to moist (inferred alluvial deposits). |
| 1879-S54 | TP18 , Depth: 1.4m | 26.4 % | ** | ** | CLAY, trace sand and gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, stiff, moist (inferred alluvial deposits). |
| 1879-S55 | TP19 , Depth: 1.3m | 21.9 % | ** | ** | CLAY, with sand & gravel, grey mottled orange/red, high plasticity, sand fine to coarse grained, gravel sub angular medium to coarse, hard, moist (inferred Haunted Hills Formation residual soil). |
| 1879-S56 | TP20 , Depth: 1.4m | 19.1 % | ** | ** | CH - CLAY, with sand & gravel, grey mottled orange/red, high plasticity, sand 20% fine to coarse grained, gravel 18% medium to coarse, hard, moist (inferred Haunted Hills Formation residual soil). |
| 1879-S57 | TP21 , Depth: 1.4m | 20.5 % | ** | ** | CLAY, trace sand, orange mottled grey, medium plasticity, sand fine to medium grained, stiff, moist (inferred alluvial deposits). |
| 1879-S58 | TP22 , Depth: 1.45m | 20.8 % | ** | ** | CLAY, with sand & gravel, grey mottled orange/red, high plasticity, sand fine to coarse grained, gravel sub angular medium to coarse, stiff, moist (inferred Haunted Hills Formation residual soil). |
| 1879-S59 | TP23 , Depth: 1.43m | 29.3 % | ** | ** | CH - CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand 13% fine to coarse grained, gravel 2%, stiff, moist (inferred alluvial deposits). |
| 1879-S60 | TP24 , Depth: 1.45m | 20.3 % | ** | ** | CLAY, with sand & gravel, grey mottled orange/red, high plasticity, sand fine to coarse grained, gravel sub angular medium to coarse, very stiff to hard, moist (inferred Haunted Hills Formation residual soil). |
| 1879-S61 | TP25 , Depth: 1.35m | 10.5 % | ** | ** | gravelly CLAY, with sand, grey mottled orange/red, medium plasticity, gravel sub angular medium to coarse, sand fine to coarse grained, hard, dry (inferred Haunted Hills Formation residual soil). |
| 1879-S62 | TP26 , Depth: 1.42m | 31.7 % | ** | ** | CLAY, trace sand & gravel, orange mottled brown, high plasticity, sand fine to medium grained, gravel fine, firm to stiff, moist (inferred alluvial deposits). |
| 1879-S63 | PTP01 , Depth: 2.1m | 31.6 % | ** | ** | sandy CLAY, trace gravel, grey mottled red/orange, high plasticity, sand fine to coarse grained, gravel fine, very stiff to hard, moist (inferred Haunted Hills Formation residual soil). |
| 1879-S64 | PTP02 , Depth: 2.0m | 15.1 % | ** | ** | CH - sandy CLAY, grey mottled red/orange, high plasticity, sand 56% fine to coarse grained, stiff, dry to moist (inferred Haunted Hills Formation residual soil). |
| 1879-S65 | PTP03 , Depth: 1.8m | 14.2 % | ** | ** | CH - sandy CLAY, trace gravel, grey mottled red/orange, high plasticity, sand 54% fine to coarse grained, gravel 1%, firm to stiff, moist (inferred Haunted Hills Formation residual soil). |

This copied document is made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright.

| Sample Number | Sample Location | Moisture Content (%) | Min | Max | Material |
|---------------|---------------------|----------------------|-----|-----|---|
| 1879-S66 | PTP04 , Depth: 2.7m | 17.5 % | ** | | sandy CLAY, trace gravel, grey mottled red/orange, high plasticity, sand fine to coarse grained, gravel fine, very stiff to hard, dry (inferred Haunted Hills Formation residual soil). |